

SPECIFICATIONS ASLC70 EXHAUST FAN WITH LIGHT



70 CFM/5.5 Sones @ 0.10" SP.

Grill

White, polymeric grill secured in place via screw mounting through the light housing, dimensions - $11" \times 10^{1}/2"$.

<u>Light Lens</u>

High impact polycarbonate lens, secured in position using integral tabs: easily removed if necessary.

Light Housing

Heavy gauge cold rolled steel c/w baked enamel finish; locks in place on the grill via two integral tabs.

Blower Wheel

One piece polymeric wheel, 41/2" diameter, 1" wide, with 10 fins.

Motor

PSC, plug-in, 4 pole motor, life time lubrication, thermally protected. Rated 120 volts, 60 hz..

Fan Housing

23 ga. Galvanized metal housing, dimensions 73/8" x 75/8" x 57/8", double metal thickness mounting tabs.

Duct Collar


Plastic collar for 4" duct connection, comes complete with built in non-metallic back draft damper for quiet operation.

Ventilating Area

For bathrooms up to 65 sq. ft. for other rooms up to 85 sq. ft.

<u>Lighting</u>

Utilizes a medium base screw in type lamp (lamp not included). Accepts up to a 15W LED, 26W CFL or 100W Incandescent type A19 lamp.



Acceptable for use over tub or shower when installed in a GFCI protected branch circuit.

Unit Mounting

Rated Type IC for ceilings insulated to R-40. Designed to mount in ceilings with at least 6" of clearance. The unit will mount using the supplied mounting bars with a rough in opening of $7^3/8$ " x $7^5/8$ ". The housing will mount through drywall thickness up to 3/4".

Single Pack Shipping Info

Box Dim: $11\frac{1}{2}$ " x $13\frac{1}{4}$ " x $9\frac{1}{2}$ " Shipping Weight: 6 lbs.

EXPANDED PERFORMANCE											
							Sones	Fan Speed	Maximum		
	Static Pressure (inches of w.g.)							@ .1 SP	RPM	Fan Watts	Amps
	0	0.05	0.1	0.125	0.15	0.2	0.25				
Air Flow - CFM	77	73	70	69	68	66	64	5.5	1725	44	1.6

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITT	SUBMITTED BY DATE		
FAN NUMBER N	MODEL Umber	CFM	IN W.G.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



Air King: 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 ● 877-304-3785 Fax: (610) 696-8048 Canada: Brampton, Ontario Tel: 905-456-2033 Fax: (905) 456-1015

Specifications subject to change without notice. Updated 1-21