



20

28"



High Speed 600 CFM/4.0 Sones @ 0.10" SP. Medium Speed 400 CFM/2.5 Sones @ 0.10" SP. Low Speed 200 CFM/0.3 Sones @ 0.03" SP.

• **Dimensions**

Overall bottom projection - 11" Height -11" Width - 28" (for 30" canopy)

• Body

Galvanized steel body with stainless steel fascia. Install at least 24 $^{\prime\prime}$ above the cooking surface.

• Blower

3 speed, thermally protected, permanently lubricated, split capacitor, 120V 60 Hz. with two electronically balanced blower wheels.

• Lighting

2 - ENERGY STAR[®] certified MR16, GU10 base 6.5 watt LED lamps, 500 lumens, JA8 compliant.

Ducting

Vertical ducting: 10" round ducting with all metal model OA10VD outlet adapter and back draft damper.

Filters

Aluminum grease filters (included).

<u>Cut Out Opening Size</u>

Width 26%" Depth - 10"



EXPANDED PERFORMANCE										
	Static Pressure (inches of w.g.)						Sones	Fan Speed	Power	
Air Flow - CFM	0	0.1	0.15	0.25	0.3	0.375	@ .1 SP	RPM	Watts	Amps
High Speed	629	600	583	540	516	475	4.0	1491	181	2.0
Medium Speed	415	400	391	371	356	325	2.5	1334	132	2.0
Low Speed	210	167	146	112	93	-	0.3	666	59.5	2.0

11"

11

