

ATW-1322

SPECIFICATIONS

Overall System

Operating Frequencies	2.4 GHz ISM band
Frequency Response	20 Hz to 20 kHz Depending on microphone type
Operating Range	60 m (200') Open range env. with no interfering signals
Dynamic Range	>109 dB (A-weighted), typical
Total Harmonic Distortion	<0.05% typical
Operating Temperature Range	0° C to +40° C (32° F to 104° F) Battery performance may be reduced at very low temperatures
Audio Sampling	24 bit / 48 kHz
Latency	3.8 ms

Receiver

Receiving System	Diversity (frequency/time/space)
Output Connectors (Microphone)	Remote Receiver Connector: RJ45 Link Connector: RJ12
Maximum Output Level	XLR, balanced: 0 dBV 1/4" (6.3 mm), unbalanced: +6 dBV
Power Supply	100-240V AC (50/60 Hz) to 12V DC 0.5A power supply switched mode external
Dimensions	209.8 mm (8.26") W x 44 mm (1.73") H x 169.3 mm (6.67") D
Weight	940g
Accessories Included	Included AC adapter, Link cable, Rack-mount adapters, Joining plate, Rubber feet

Handheld Transmitter

RF Power Output	10 mW
Spurious Emissions	Following federal and national regulations
Battery Type	Two 1.5V AA (not included)

Handheld Transmitter

Battery Life	>7 hours (alkaline) (Depending on battery type and use pattern)
Dimensions	254.8 mm (10.03") long, 50.0 mm (1.97") diameter
Net Weight	280g
Accessories Included	AT8456a Quiet-Flex™ stand clamp