




2MP 3 Axis Vandal Proof Dome Camera

IV-6100HD


Features:

- . 1/3" Panasonic 2.1M CMOS
- . 1080p / 720p
- . 2.8 ~ 11mm Auto iris IR-CUT lens
- . Day& Night
- . White Balance
- . Controlled by OSD Menu

EXTERNAL ZOOM / FOCAL ADJUSTMENT



PANNING UPTO 360°



TILTING 10°~90°



SPECIFICATION	IV-6100HD
Image Sensor	1/3" Panasonic 2.1M CMOS
Sync. System	Internal / External (V-Lock)
Minimum Illumination	Color: 1.0 Lux, BW: 0.5 Lux, Color DSS: 0.002 Lux, BW DSS: 0.001 Lux
Resolution	1080p / 720p
S/N Ratio	More than 50dB (AGC off)
Exposure	Auto / Manual
Shutter Speed	N: 1/30 ~ 1/60000 sec; P: 1/25 ~ 1/60000 sec
Digital Slow Shutter	Off / Max x2 ~ x8
Gain Control	Off / On (Max 30 dB)
Flickerless	Off / On
HR	Off / 1 ~ 10 steps
Intelligent	Privacy / MD / OD
Brightness	1 ~ 20 steps
Day& Night	Auto / Color / B&W / Ext
White Balance	Auto / Autoext / Preset / Manual
Image Sensor	HLC / DNR / HR / Mirror / Sharpness / Effect / Freeze / E.Zoom
BLC	Off / BLC / HLC / D-WDR
Mirror	Off / On
DNR	Off / Low / Middle / High
FLIP	Off / On
Sharpness	1 ~ 10 steps
E.Zoom	E-Zoom (Max x1.1 ~ 8.0)
Privacy Mask	Area option
Motion Detection	Area option
Object Detection	Off / On
Sync Mode	INT / LL
Phase	N: 0 ~ 131 steps; P: 0 ~ 156 steps
DIS	Off / On
Defect Det	One Push
Display	Disp Sel / Set Title / Language / Setup Status
Comm	Baud Rate: 2400 / 4800 / 9600 / 19200 / 38400 / 57600 / 115200
Protocol	Pelco-D / Pelco-P
Storage Temperature	-4 °F to 140°F (-20°C to 60°C)
Disp Sel	ID / Title / Zoom Ratio
Set Title	Text Edit
Language	English / Chinese
Setup Status	Setup Status List
OSD Text	0 ~ 9, A ~ Z, a ~ z
Operating Temperature	14 °F to 122°F (-10°C to 50°C)
Operating Humidity	0 ~ 86% (non-condensing)
IR-CUT Filter	Available
Power Consumption	DC 12V / Max: 450mA
LED Quantity	36 PCS Ø5
Lens Mount	2.8 ~ 11mm Auto iris IR-CUT lens
IR Range	25 ~ 35 m
Weight	appx. 1.63 lbs
Dimensions	4.7"(W) x 4"(D) / 120(W)mm x 96(D)mm