ElectroVoice | EVOLVE 50 Portable Column System

EVOLVE 50 Portable Column System




- EV QuickSmart Mobile application: quickly and wirelessly configure, control, and monitor up to six EVOLVE 50 systems simultaneously, and receive immediate notification during critical performance conditions. *Bluetooth® connectivity is available in select countries.*
- High-quality Bluetooth[®] audio streaming for background music or musical accompaniment. Bluetooth[®] connectivity is available in select countries.
- Ultra-wide 120° horizontal coverage via customdesigned waveguides and array-formed 40° asymmetrical vertical coverage means all acoustical energy is directed towards both sitting and standing audiences.
- QuickSmartDSP provides best-in-class processing via EV's signature single-knob user interface with LCD.
- Ideal for portable applications. Light weight and intuitive assembly via the magnet assisted sub pole make a quality performance easier than ever.

The EVOLVE 50 Portable Column System is a three component loudspeaker system powered by a 1000 W Class-D amplifier and driven by Electro-Voice's QuickSmartDSP.

The system consists of a 15 mm wooden, ported, powered subwoofer enclosure that houses a 12" subwoofer capable of a functional frequency output down to 37 Hz.

The bi-directional aluminum pole's connection to the subwoofer is secured using a magnet, and the column array is gravity-held to the sub pole. The signal is internally routed to the components.

Eight 3.5" neodymium drivers in the column array coupled with the 12" subwoofer delivers up to 127 dB SPL. The eight composite waveguides control highfrequencies with 120° of horizontal coverage, and 40° of asymmetrical (down-facing) vertical coverage to



ensure suitable output for sitting and standing audiences. The sub pole and column array come prepackaged in a carrying bag.

The processing engine allows for easy setup via four presets (Music, Live, Speech, and Club), three-band EQ, five user-programmable presets (Store and Recall settings), output delay, phantom power (+15V), visual monitoring of limiter status, input level control and meters, and master volume control to ensure optimal gain structure.

The new Electro-Voice QuickSmart Mobile application utilizes Bluetooth® Low Energy (BTLE) technology for the wireless configuration, control, and monitoring of up to six EVOLVE 50 systems simultaneously. Highresolution Bluetooth® audio streaming adds convenience for wireless music playback in breakout rooms, intermission, and musical accompaniment. Bluetooth[®] is available in select countries.


Parts included

Technical specifications


Frequency response (-3 dB) ¹ :	43 Hz-20 KHz
Frequency range $(-10 \text{ dB})^1$:	37 Hz-20 KHz
Maximum SPL ² :	127 dB
Coverage (H x V):	120° x 40°
Amplifier rating:	1000 W
LF channel rating:	500 W
HF channel rating:	500 W
Crossover frequency:	200 Hz
Connectors:	2x XLR/TRS Combo Jack Input 1x 3.5 mm Input 1x Stereo RCA Input 1x Wireless Bluetooth® Audio Input 1x XLR THRU Output 1x XLR MIX OUT Output
Enclosure:	Sub: 15 mm plywood Column: Composite Pole: Aluminum
Grille:	Steel with black or white powder coat
Color:	Black or white
Dimensions (HxWxD): mm (in)	Sub: 530 x 345 x 471 (20.9 x 13.6 x 18.5) Column: 825 x 102 x 172 (32.5 x 4.0 x 6.9) Pole: 929 x 48.5 x 55 (36.6 x 1.9 x 2.2)
Net weight:	Sub: 44.66 lb (20.3 kg) Column: 10.34 lb (4.7 kg) Pole: 2.75 lb (1.25 kg) Sub cover: 0.9 lb (0.4 kg)
01	Bag for column and pole: 1.87 (0.85 kg)
Shipping weight:	Sub box: 50.71 lb (23 kg) Column box: 18.30 lb (8.3 kg)
Power consumption ³ :	100-240 V AC, 50-60 Hz, 1.5-0.6 A
¹ Full-space measurement	using music DSP preset


¹Full-space measurement using music DSP preset. ²Maximum SPL is measured at 1 m using broadband pink noise at maximum output. ³Current rating is 1/8 power.

Frequency response:



Dimensions:







102 mn [4.0 in]

825 mm [32.5 in]

[1 8







470 mm [18.5 in]

Ordering information

EVOLVE50-TB Column speaker array, pole, black EVOLVE 50 column array, sub pole, and carrying bag, black Order number **EVOLVE50-TB | F.01U.335.090**

EVOLVE50-SB-US Column speaker sub US, black EVOLVE 50 column subwoofer, US, black Order number **EVOLVE50-SB-US | F.01U.335.091**

EVOLVE50-SB-EU Column speaker sub EU, black EVOLVE 50 column subwoofer, EU, black Order number **EVOLVE50-SB-EU | F.01U.335.094**

EVOLVE50-SB-AP Column speaker sub AP, black EVOLVE 50 column subwoofer, AP, black

Order number EVOLVE50-SB-AP | F.01U.335.097

EVOLVE50-SB-GL Column speaker sub, black, global, no BT

EVOLVE 50 column subwoofer, global, no BT, black Order number **EVOLVE50-SB-GL | F.01U.335.092**

EVOLVE50-TW Column speaker array, pole, white EVOLVE 50 column array, sub pole, and carrying bag,

white Order number EVOLVE50-TW | F.01U.335.099

EVOLVE50-SW Column speaker sub, white, global w BT EVOLVE 50 column subwoofer, global, white Order number EVOLVE50-SW | F.01U.335.100

EVOLVE50-SW-GL Column speaker sub, white, global, no BT

EVOLVE 50 column subwoofer, global, no BT, white Order number EVOLVE50-SW-GL | F.01U.335.101

Represented by:

Germany: Bosch Sicherheitssysteme GmbH Robert-Bosch-Ring 5 85630 Grasbrunn Germany www.electrovoice.com

Bosch Security Systems, LLC 12000 Portland Avenue South Burnsville MN 55337 USA

@ Bosch Security Systems2021 | Data subject to change without notice | 202105201628 | V5 | May 20, 2021

Accessories

EVOLVE50-SUBCVR Subwoofer cover Cover for the EVOLVE 50 subwoofer, black Order number EVOLVE50-SUBCVR | F.01U.336.241

EVOLVE50-CASE Column speaker carrying case, wheels Column speaker carrying case with wheels, black Order number **EVOLVE50-CASE | F.01U.335.110**

EVOLVE50-PL-SB Column speaker pole, short, black Column speaker short pole, black Order number EVOLVE50-PL-SB | F.01U.335.108

EVOLVE50-PL-SW Column speaker pole, short, white Column speaker short pole, white Order number EVOLVE50-PL-SW | F.01U.335.109