

# IPEG-B20F-IRW2

## 2MP Starlight Bullet Network Camera



- 2MP, 1/2.7" CMOS image sensor, low illuminance, high image definition
- H.265&H.264 dual-stream encoding
- 2MP (1920 × 1080)@25/30 fps
- DWDR, 3D DNR, HLC, BLC
- 2.8 mm fixed lens
- Starlight Support, Max. IR LEDs Length 98ft
- 256GB Micro SD memory, IP67, PoE

## System Overview

IC Realtime's new IPEG-B20F-IRW2 is a bullet style camera in the budget friendly Edge lineup. This camera is equipped with high end features including H.265 encoding and Starlight support with DWDR for a more colorful image in daylight as well as low illumination environments and Smart IR support with up to 98ft of illumination.

The camera supports H.265 encoding technology, which provides a more efficient video encoding capacity, and saves bandwidth and storage space compared to H.264. In addition, it supports 256GB SD card storage and is waterproof and dust-proof by complying to IP67 standards.

## Functions

### Starlight Technology

Featuring Starlight Technology, this camera is ideal for applications with challenging lighting conditions. Its low-light performance delivers usable video with minimal ambient light. Even in extreme low-light conditions, Starlight Technology is capable of delivering color images in near complete darkness (0.005 lux).

### Environmental

Cameras operate in extreme temperature environments, rated for use in temperatures from -40° F to +140° F (-40° C to +60° C) with 95% humidity.

### Smart H.265+

Deliver high quality video without straining the network, Smart H.265+ is the optimized implementation of H.265. The Smart H.265+ encoding technology includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing saving of up to 70% of bandwidth and storage when compared with standard H.265.

### Protection (IP67)

The camera's outstanding reliability is unsurpassed due to its rugged design. The camera is protected against water and dust with IP67 ranking, making it suitable for indoor or outdoor environments

### Interoperability

The camera conforms to the ONVIF (Open Network Video Interface Forum) specifications, ensuring interoperability between network video products regardless of manufacturer.

### Smart IR Technology

With IR illumination, detailed images can be captured in low light or total darkness. The camera's Smart IR technology adjusts the intensity of camera's infrared LEDs to compensate the distance of an object. Smart IR technology prevents IR LEDs from whitening out images as they come closer to the camera. The camera's integrated infrared illumination provides high performance in extreme low-light environments up to 98ft (30m).

## Technical Specification

### Camera

Image Sensor	1/2.7" 2 Megapixel progressive CMOS
Effective Pixels	1920(H) x 1080(V), 2 Megapixels
RAM/ROM	128MB /128 MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s-1/100000 s
Minimum Illumination	0.005 Lux @ F1.6
S/N Ratio	More than 50dB
IR Distance	Distance up to 98.43 ft (30 m)
IR On/Off Control	Auto / Manual
IR LEDs	1

### Lens

Lens Type	Fixed				
Mount Type	M12				
Focal Length	2.8mm				
Max. Aperture	F1.6				
Angle of View	Horizontal: 110.0°, Vertical: 59.0°				
Optical Zoom	N/A				
Focus Control	Fixed				
Close Focus Distance	1.97 ft (0.6 m)				
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	122ft	48ft	24ft	12ft

### Pan/Tilt/Rotation

Pan/Tilt/Rotation Range	Pan: 0°-360°Tilt: 0°-90°Rotation: 0°-360°
-------------------------	---

### Video

Compression	H.265; H.264; H.264B; MJPEG (Sub stream only)
Streaming Capability	2 Streams
Resolution	1080P(1920x1080)/1.3M(1280x960)/720P(1280x720)/D1(704x576/704x480)/VGA(640x480)/CIF(352x288/352x240)
Frame Rate	Main Stream: 1920 x 1080 (1 fps-25/30 fps) Sub Stream: 704 x 576 (1 fps-25fps) 704 x 480 (1 fps-30fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 32 kbps-6144 kbps H.265: 12 kbps-6144 kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / DWDR
White Balance	Auto/natural/street lamp/outdoor/manual/regional custom
Gain Control	Auto / Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Smart IR	Support

Starlight	Support
Digital Zoom	16x
Flip	0°/90°/180°/270°)
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

### Audio

Compression	N/A
-------------	-----

### Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	IPv4; IPv6; HTTP; HTTPS; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; 802.1x; Bonjour
Interoperability	ONVIF(Profile S/Profile G/Profile T);CGI; P2P
Streaming Method	Unicast / Multicast
Max. User Access	20
Edge Storage	FTP; SFTP; Micro SD Card (support max. 256 GB); NAS
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	SmartICRSS, DSS
Smart Phone	IOS, Android

### Certifications

Certifications	CE-LVD: EN60950-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart BUL/CUL: UL60950-1 CAN/CSA C22.2 No.60950-1-07
----------------	---

### Interface

Video Interface	N/A
Audio Interface	N/A
RS485	N/A
Alarm	N/A

### Electrical

Power Supply	DC12V, PoE (802.3af)
Power Consumption	<4.6W

### Environmental

Operating Conditions	-40°F to +140°F (-40°C to +60°C)/less than ≤ 95% RH
Storage Conditions	-40°F to +140°F (-40°C to +60°C)
Ingress Protection	IP67
Vandal Resistance	N/A

### Construction

Casing	Metal
Dimensions	6.54" x 2.76" (166.2 mm x 70 mm)
Net Weight	1.1 lb (0.48 kg)
Gross Weight	1.3 lb (0.57 kg)

Accessories

Dimensions (mm/in)

MNT-JUNCTION BOX 3

