

IPMX-W40F-IRW2

4MP Starlight Mini Wedge Network Camera



- 1/3" 4 Megapixel progressive scan CMOS
- H.265 & H.264 triple-stream encoding
- 30fps @4MP(2688 × 1520)
- Intelligent Motion Detect and Perimeter Protection
- WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC
- 2.8mm fixed lens, Built-in Mic
- Starlight support, Max IR LED Length 164 feet
- 256GB Micro SD memory, IP67, IK10, PoE

System Overview

The IPMX-W40F-IRW2 is the newest wedge dome in the Max line of cameras updated with the newest AI features. This small form factor camera adopts a 4MP, 1/3" Megapixel progressive scan CMOS sensor enabling 4 Megapixel video at up to 30FPS. This sensor is paired with a 2.8mm fixed lens, and Starlight supported with IR LEDs capable of illumination up to 164'. The image sensor itself has a strong 120 dB dynamic range, making this dome camera a 'True WDR' camera. The camera also supports audio with a built-in mic.

The real magic of this camera lies in its new AI (Advanced Intelligence) suite of features, which includes: Intelligent Motion Detect and Perimeter Protection. These features combined with our AI line of recorders provide extra reduction in false positives and efficiency using the search function.

Made in South Korea and conforms to the Trade Agreements Act (TAA).

Functions

Starlight Technology

Featuring Starlight Technology, this camera is ideal for applications with challenging lighting conditions. Its low-light performance delivers usable video with minimal ambient light. Even in extreme low-light conditions, Starlight Technology is capable of delivering color images in near complete darkness (0.005 lux).

iMD (Intelligent motion Detect)

This is an upgraded version of motion detection currently known as Intelligent Motion Detection (iMD). The upgraded Plus version greatly improves alarm accuracy by pre-loading a deep learning algorithm that recognizes people and vehicles. Motion detection alerts containing a human and/or vehicle intrusion event are now possible with up to 95% accuracy. Eliminate false alarms, save time and keep stress levels low knowing you're protected.

Wide Dynamic Range (WDR)

The camera achieves vivid images, even in the most intense contrast lighting conditions, using industry-leading wide dynamic range (WDR) technology. For applications with both bright and low lighting conditions that change quickly, True WDR (120 dB) optimizes both the bright and dark areas of a scene at the same time to provide usable video.

Perimeter Protection

IC Realtime's Perimeter Protection features significantly improve detection accuracy. The benefits of Perimeter Protection include up to a 90% reduction in false alarms. Other advantages include a decrease in pixel count requirement for object detection, which translates into more efficiency with less strain on the system. Perimeter Protection options let you customize tripwires based on the object type and allow intelligent automation within a limited area of access such as pedestrian or vehicle-only zones. The combination of advanced AI analytics and real-time alerts maximizes efficiency & balance of the total systems capacity and resources resulting in greater surveillance system efficiency.

Smart H.265+

Deliver high quality video without straining the network, Smart H.265+ is the optimized implementation of H.265. The Smart H.265+ encoding technology includes a scene adaptive encoding strategy, dynamic GOP, dynamic ROI, flexible multi-frame reference structure and intelligent noise reduction, providing saving of up to 70% of bandwidth and storage when compared with standard H.265.

Protection (IP67, IK10, wide voltage)

The camera allows for $\pm 25\%$ input voltage tolerance, suitable for the most unstable conditions for outdoor applications. Its 2KV lightning rating provides effective protection for both the camera and its structure against lightning. Subjected and certified to rigorous dust and immersion tests (IP67) and impact tests (IK10), The camera complies with an IK10 impact rating making it capable of withstanding the equivalent of 5 kg (11.02 lbs) of force dropped from a height of 40 cm (15.75 in.)

Technical Specification

Camera

Image Sensor	1/3"4 Megapixel progressive CMOS
Effective Pixels	2688 (H) ×1520 (V)
RAM/ROM	512MB/128MB
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual 1/3 s–1/100000 s
Min. Illumination	0.005 Lux@F1.6
S/N Ratio	> 56 dB
IR Distance	50 m (164.0 ft)
IR On/Off Control	Auto / Manual
IR LEDs	8

Lens

Lens Type	Fixed			
Mount Type	M12			
Focal Length	2.8mm			
Max. Aperture	F1.6			
Angle of View	Horizontal:103°; vertical: 55°;			
Optical Zoom	N/A			
Focus Control	Fixed			
Close Focus Distance	0.9 m (3.0 ft)			
DORI Distance	Detect	Observe	Recognize	Identify
	183ft	73ft	36ft	18ft

Pan/Tilt/Rotation

Pan/Tilt/Rotation Range	Pan: -30°–30°; Tilt: 0°–80°; Rotation: 0° to 360°
-------------------------	---

Intelligence

Perimeter Protection	Tripwire; intrusion (Recognition of human and vehicle) Works together with Smart NVRs to perform refined intelligent search, event extraction and merging to event videos
Intelligent Motion Detect	Support

Video

Compression	H.265; H.264; H.264H; H.264B; MJPEG (sub stream only)
Smart Codec	Smart H.265+/ Smart H.264+
Streaming Capability	3 Streams
Resolution	4M (2688 × 1520); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
Frame Rate	Main Stream (2688 × 1520@1–25/30 fps) Sub Stream:(704 × 576@1–25 fps/ 704 × 480@1–30 fps) Third Stream: (1280 × 720@1–25/30 fps)
Bit Rate Control	CBR/VBR
Bit Rate	H.264: 3 Kbps–8192 Kbps H.265: 3 Kbps–8192 Kbps
Day/Night	Auto(ICR) / Color / B/W
BLC Mode	BLC / HLC / WDR(120dB)
White Balance	Auto/Natural/Street Lamp/Outdoor/Manual

Gain Control	Auto / Manual
Noise Reduction	3D DNR
Motion Detection	Off / On (4 Zone, Rectangle)
Region of Interest	Off / On (4 Zone)
Electronic Image Stabilization (EIS)	N/A
Smart IR	Support
Flip	0°/90°/180°/270° (Support 90°/270° with 1920 × 1080 resolution and lower.)
Mirror	Off / On
Privacy Masking	Off / On (4 Area, Rectangle)

Audio

Compression	G.711a; G.711Mu; G726; AAC
-------------	----------------------------

Network

Ethernet	RJ-45 (10/100Base-T)
Protocol	Pv4;IPv6;HTTP;HTTPS;TCP;UDP;ARP;RTP;RTSP;RTCP; RTMP;SMTP;FTP;SFTP;DHCP;DNS;DDNS;QoS;UPnP;NTP;Multicast;IGMP;NFS;PPPoE;802.1x;SNMP
Interoperability	ONVIF(Profile S/Profile G);CGI;P2P
Scene Self-adaptation	Support
Max. User Access	20 (Total bandwidth: 64 M)
Edge Storage	NAS Local PC for instant recording Micro SD card 256GB
Web Viewer	IE, Chrome, Firefox, Safari
Management Software	SmartICRSS, DSS
Smart Phone	IOS, Android

Certifications

Certifications	CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B
----------------	---

Interface

Video Interface	N/A
Audio Interface	Built-in Mic
RS485	N/A
Alarm	N/A

Electrical

Power Supply	DC12V, PoE (802.3af)
Power Consumption	<5.7W

Environmental

Operating Conditions	-40°C to +60°C (-40°F to +140°F)/less than 95%
Storage Conditions	-40°C to +60°C (-40°F to +140°F)
Ingress Protection	IP67
Vandal Resistance	IK10

Construction

Casing	Metal
Dimensions	55 mm × 108.9 mm (2.2" × 4.3")
Net Weight	380 g (0.8 lb)
Gross Weight	520 g (1.1 lb)

Accessories

Dimensions (mm/in)

