



2-Port Power Delivery Mini Car Charger - 25 W

USB-C Power Delivery Port up to 25 W, USB-A QC 3.0 Charging Port up to 18 W, Black

Part No.: [102414](#)

EAN-13: 0766623102414 | UPC: 766623102414

Power up your devices with a powerful Power Delivery car charger

Enjoy incredible mobile charging power with the Manhattan 2-Port Power Delivery Mini Car Charger - 25 W. The USB-C port's Power Delivery (PD) technology determines the power needs of your connected MacBook®, smartphone, tablet, handheld game console or other device and delivers it at the fastest, safest rate. The additional USB-A port fast charges an additional handheld device with QC 3.0 technology, which returns your device to full power far quicker than a standard charger. No matter your vehicle, this compact charger fits most 12 - 24 V auxiliary power sockets, so it's the perfect power companion to have on hand for when your devices' batteries are low and a standard wall outlet is not available. The Manhattan 2-Port Power Delivery Mini Car Charger - 25 W also intelligently protects itself and your devices from short-circuits, overvoltage, overcurrent and overheating.

Features:

- Two-device charging solution with USB-C Power Delivery (PD 3.0) and USB-A QC 3.0 charging ports
- Charges two different devices simultaneously with total power up to 25 W

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- USB-C Power Delivery (PD) port delivering up to 25 W
- USB-C Power Delivery (PD) port delivering up to 25 W to charge a smartphone, tablet, GPS, handheld game console and more
- USB-A QC 3.0 charging port delivering up to 18 W
- Overload, overcurrent and overheat protection
- Ultra-compact, portable and lightweight design for easy travel
- Fits most vehicles' 12 - 24 V auxiliary power socket
- Three-year warranty

Specifications:

Standards and Certifications

- PD 3.0
- Qualcomm QC 3.0
- CE
- RoHS
- FCC

Electrical

- DC input: 12 - 24 V; 50 - 60 Hz
- Voltage/current settings (maximum):
 - USB-C PD 25 W output:
 - 5 V / 3 A
 - 9 V / 3 A
 - 12 V / 2.5 A
 - 15 V / 2 A
 - 20 V / 1.5 A
 - USB-A QC 3.0 18 W output:
 - 4.5 V / 5 A
 - 5 V / 4.5 A
 - 9 V / 3 A
 - 12 V / 2.5 A

Protection Characteristics

- Short-circuit (SCP) with auto-recovery mode
- Overvoltage (OVP) with auto-recovery mode
- Overcurrent (OCP) — current limit: 150% (max)
- Over-temperature (OTP)

Physical

- Dimensions: 45 x 26 x 26 mm (1.77 x 1.02 x 1.02 in.)
- Net weight: 20 g (0.71 oz.)
- Gross weight: 65 g (2.29 oz.)
- Housing: plastic

Operating Environment

- Operation temperature: -20 - 55°C (-4 - 131°F)

