



Passive Mini DisplayPort to HDMI Adapter

Mini DisplayPort Male to HDMI Female, 1080p@60Hz, White

Part No.: [151399](#)

EAN-13: 0766623151399 | UPC: 766623151399

Easily connect a mini-DisplayPort source to an HDMI cable

The Manhattan Mini DisplayPort to HDMI Adapter establishes a fast and convenient connection between a mini-DisplayPort media source and an HDMI display cable. Ideal for presentations, retail displays and other uses, this single-cable solution keeps installations and workplaces neat and organized without an external power supply or complicated configuration. Nickel-plated contacts and full shielding help the Manhattan Mini DisplayPort to HDMI Adapter provide a clear and stable video transmission in home and office multimedia applications. A durable, white PVC jacket and molded boots with strain relief complement Macintosh systems and help ensure connections remain uninterrupted and steady.

Features:

- Connects a Mini DisplayPort source with an HDMI display cable
- Supports 1080p@60Hz resolution
- Delivers a single, high-quality signal to an HDMI display — ideal for Mac computers
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

Specifications:

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Standards and Certifications

- UL 20276
- DisplayPort v1.2
- HDMI 1.3

General

- 8-bit and 10-bit Deep Color support
- 10.8 Gbps bandwidth
- Auxiliary channel support, 1 Mbps
- One-lane, one-direction, four-line connection support
- Passive

Connections

- Mini DisplayPort 20-pin male
- HDMI 19-pin female
- Nickel plated
- Molded PVC boot
- Shielded

Cable

- 30 AWG connectors
- Shielding: Mylar and aluminum
- Withstanding voltage: 300 VDC
- Insulation resistance: 5 MOhm
- Conductive resistance: 10 Ohm
- Thermal plastic casing
- Length: 12cm

Physical

- Length: 17 cm (6.7 in.)
- Weight: 0.05 g (0.12 lbs.)

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8/8.1/10, Linux or Mac 9.x/10.x or above
- DP++ (dual-mode) video/graphics card

Package Contents

- Passive Mini DisplayPort to HDMI Adapter

