



4K@30Hz USB-C to HDMI Adapter

USB 3.2 Type-C Male to HDMI Female Converter, Black

Part No.: [151788](#)

EAN-13: 0766623151788 | UPC: 766623151788

USB C to HDMI Adapter - easily connect a USB-C source with an HDMI display

The Manhattan USB-C to HDMI Converter establishes a fast, simple and convenient link between a newer USB type-C equipped media source (computer, tablet, etc.) and an existing HDMI display (monitor, projector, etc.). The Manhattan USB-C to HDMI Converter is easy and quick to install — no complicated configuration or setup required. Its all-in-one design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly. Extend the service life of your equipment, and fully realize the investment and value of your HDMI display, projector or peripheral with the Manhattan USB-C to HDMI Converter.

Features:

- Converts USB-C video and audio to an HDMI signal
- Delivers Ultra-High-Definition (UHD) images on an HDMI monitor, projector or other display device
- Supports video resolutions up to 3840x2160p@30Hz
- Compliant with DisplayPort 1.2 Alternate Mode (DP Altmode)
- Plug and Play; requires no external power supply
- Compatible with all USB type-C supported desktops, notebooks and tablets including Apple MacBook, Chromebook Pixel and more
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Specifications:

Standards and Certifications

- USB 3.2 Gen 1
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE

Connections

- USB type C, 24-pin, male
- HDMI, 19-pin, female
- Shielded

Video Resolutions

- 640x480, 800x600, 1024x768, 1920x1200, 3840x2160p@30Hz

Physical

- 32-AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Cable length: 15 cm (6 in.)
- Weight: 31 g (1.1 oz.)
- Shielded
- Housing: ABS plastic

Operating Environment

- Operation Temperature: 0 - 50°C (32 - 122°F)
- Storage Temperature: -40 - 85°C (-4 - 185°F)
- Humidity (noncondensing): 0 - 96%

System Requirements

- Windows XP/Vista/7/8.1/10/11 or Linux or Mac 9.x/10.x or above

Package Contents

- USB-C to HDMI Converter

This product is part of a group; the complete list of variations follows:

- #153690 - USB-A to HDMI
- #151788 - USB-C to HDMI, 4K@30Hz
- #153416 - USB-C to HDMI, 4K@60Hz, PD Port

