



SuperSpeed USB-C Multiport Adapter

USB 3.2 Type-C Male to HDMI (4K@30Hz) Female, Two USB 3.0 Type-A Ports, USB-C Power Delivery (PD) Port, Gigabit RJ45 Port, SD Card Reader; Aluminum, Gray

Part No.: [152075](#)

EAN-13: 0766623152075 | UPC: 766623152075

Give your USB type-C device easy network connectivity and get the perfect connection to your HDMI display, USB peripherals and SD memory card, too.

The Manhattan SuperSpeed USB-C Multiport Adapter establishes a fast, simple and convenient link between a newer USB type-C-equipped media source (computer, tablet, smartphone, etc.) and an existing HDMI display (monitor, projector, etc.), in either mirror or extended display mode. This hub creates a mini-workstation by adding two of any USB 3.0 (and earlier) peripheral, such as a mouse, keyboard, hub, external memory device and more using the integrated USB-A ports, Gigabit network connection and SD card slot.

The Manhattan SuperSpeed USB-C Multiport Adapter is easy and quick to install. No complicated configuration or setup is required to enhance the functionality of your type-C device. Its design achieves a compact, integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Features:

- Connects a USB type-C device to one HDMI display, two USB 3.0 type-A devices, Ethernet access through one 10/100/1000 Mbps RJ45 port, ample power for attached devices through one USB-C Power Delivery

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- (PD) port and one memory card through one SD card reader
- Delivers Ultra-High-Definition (UHD) video and audio to an HDMI monitor, projector or other display device
- Mirror or extended-display modes to support video resolutions up to 1080p@60Hz (1080p) or 3840x2160 at 30 Hz (4K, Full UHD)
- One Gigabit Ethernet (10/100/1000 Mbps) port for faster downloads, media streaming and gaming
- Two USB 3.0 type-A ports to connect mice, keyboards or portable memory devices (and more) or to charge and sync portable electronic devices
- USB-A SuperSpeed port offering 5 Gbps data transmission speeds
- Easy access to media and content management with read/write/copy SD port; supports automatic card detection and data transfer speeds up to 40 Mbps
- USB-C PD port for a maximum of 60 W (20 V at 5 A)
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger – available from Manhattan
- Durable aluminum housing, making it the perfect desktop or travel companion
- Compatible with all USB-C DP-Alt-Mode-supported desktops, notebooks and tablets including Apple MacBook[®], iPad[®] Pro, Chromebook[™], Pixel[™] and more
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and Play
- Molded PVC boot and strain relief
- Three-year warranty

Specifications:

Standards and Certifications

- USB 3.2
- HDMI
- HDCP 1.4
- CE
- FCC
- RoHS2
- WEEE
- UKCA

General

- Video Resolutions: 640 x 480, 800 x 600, 1024 x 768, 1920 x 1200, 1080p, 3840 x 2160p at 30 Hz, 4K
- USB-A ports: 5 Gbps
- Supported flash cards: SD / SDHC / SDXC / EXTREME SD / EXTREME II SD / EXTREME III SD / ULTRA SD / ULTRA II SD / ULTRA II SD P PLUS / SD-ULTRA-X / ULTRA SPEED SD / SD PRO / SD ELITE PRO / HS SD / MMC / MMC 4.0 / HS MMC / HS RS MMC / RS MMC / RS MMC 4.0 / MMC Mobile

- Supported flash cards: SD, SDHC and SDXC; up to 128 GB
Transfer speed: up to 40 Mbps
- 34-AWG cable gauge
- Bus powered
- USB-C PD Charging Port: 60 W (20 V at 5 A)
- USB-A Total Output: 5 V, 2 A
- Mylar and aluminum shielding
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm

Connections

Input:

- One USB-C 24-pin, male

Outputs:

- One HDMI 19-pin, female
- One 10/100/1000 Mbps RJ45, female
- Two USB-A 4-pin, female
- One SD memory slot
- One USB-C 24-pin, Power Delivery, data sync, female

Physical

- Housing: 116 x 45 x 15 mm
- Cable Length: 13 cm (5.11 in.)
- Weight: 83 g (2.92 oz.)
- Housing: aluminum

Operating Environment

- Operation Temperature: 0 – 45°C (32 – 113°F)
- Storage Temperature: -10 – 70°C (14 – 158°F)
- Humidity (noncondensing): 10 – 90%

System Requirements

- Windows XP/Vista/7/8.1/10 or Linux or Mac 10.7.1 or above

Package Contents

- SuperSpeed USB-C Multiport Adapter
- Quick Instruction Guide

