



## USB-C to HDMI Adapter Cable

Converts a DP Alt Mode Signal to an HDMI 4K Output, 1 m (3 ft.), Black

Part No.: [152235](#)

EAN-13: 0766623152235 | UPC: 766623152235

Easily convert a USB-based Audio/Video signal into HDMI format.

The Manhattan USB-C to HDMI Adapter Cable transmits a USB audio/video signal to an HDMI projector, flat-panel display, television or similar device. Built-in circuitry allows digital media enthusiasts to easily enjoy USB-based multimedia content on an Ultra High Definition (UHD) display while maintaining simultaneous A/V reception at the source. Its UHD capability supports up to 3840x2160@30Hz and 4K to serve a wide range of resolutions in many devices and UHD applications including training, retail and trade show settings. Your source device must support DP Alt Mode. No additional setup is required. It effortlessly delivers digital content that is stored on a smartphone, tablet, Ultrabook or notebook computer to a display with HDMI input capabilities.

### Features:

- Easily connects a USB-C DP Alt Mode device to an HDMI display, monitor or projector
- Delivers clear, sharp resolution up to 3840x2160 @30Hz; supports 4K Ultra HD video aspect ratio of 21:9
- Ideal for connecting an HDMI display to a DP Alt Mode-capable smartphone, tablet, Ultrabook, laptop and more
- Compatible only with a USB-C device that supports DP Alt mode; Thunderbolt 3 port compatible
- Slim design makes for a clutter-free desktop; direct-connect cable

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

makes it the perfect travel companion

- Also available in 2m (6 ft.) length [search part number 151764 at [www.manhattanproducts.com](http://www.manhattanproducts.com)]
- Bus powered: no external power supply needed
- Three-year warranty

## **Specifications:**

### Standards and Certifications

- CE
- FCC
- RoHS2
- USB 3.1
- HDMI
- HDCP
- DP Alt Mode

### General

- Supports lane data rates of 2.7 Gbps High Bit Rate (HBR) and 1.62 Gbps Reduce Bit Rate (RBR)
- Resolution: up to 3840x2160@30Hz
- Audio and video output through HDMI
- Bus powered: no external power supply
- Supports HDCP pass-through

### Connections

- Input: USB 3.1 type-C male
- Output: HDMI type-A male

### Physical

- Adapter cable: 1 m (3 ft.)
- Weight: 0.09 kg (3.2 oz.)

### Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

### System Requirements

- DP Alt Mode-supported device

### Package Contents

- USB-C to HDMI Adapter Cable

