



Passive Mini DisplayPort to DVI-I Adapter

Mini DisplayPort Male to DVI-I Dual-Link Female, White

Part No.: [152907](#)

EAN-13: 0766623152907 | UPC: 766623152907

Easily connect a single-mode Mini DisplayPort source to a DVI-I cable

The Manhattan Passive Mini DisplayPort to DVI-I Adapter establishes a fast and convenient connection between a media source equipped with Mini DisplayPort and a DVI display cable. This passive adapter requires a DP++ (dual-mode) video/graphics card to regenerate the signal and ensure the best connection to an HD display. Nickel-plated contacts and full shielding help the Manhattan Passive Mini DisplayPort to DVI-I Adapter provide clear and stable video transmissions in HD, home and office multimedia applications. Durable PVC jackets and molded boots with strain relief help ensure connections remain uninterrupted and steady.

Features:

- Connects a Mini DisplayPort source to a DVI-I display cable; compatible with DVI-D single link
- Delivers a single, high-quality signal to a DVI display — ideal for PCs and Macs equipped with Mini DP++ ports
- Passive adapter requires DP++ (dual-mode) video/graphics card to regenerate the signal and ensure the best connection to an HD monitor, projector or other video media type
- Ideal for gaming, digital signage, financial and other markets
- Supports resolutions up to 1080p@60Hz and DisplayPort 2.7 Gbps over four lanes
- Compatible with DVI-I and DVI-D interfaces
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

Specifications:

Standards and Certifications

- FCC
- CE
- RoHS2
- UL 20276
- DisplayPort v1.1a

General

- Passive Mini DisplayPort conversion
- Maximum single-link range: 1080p@60Hz resolution
- 32 AWG connectors

Connectors

- One Mini DisplayPort 20-pin male
- One DVI-I Dual Link 29-pin female
- Nickel plated
- Molded PVC boot
- Shielded

Physical

- Dimensions: 4.5 x 1.5 x 19.5 cm (1.8 x 0.6 x 7.7 in.)
- Weight: 34 g (0.03 oz.)
- Housing: plastic
- Cable length: 18.5cm

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 65°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10 or Mac OS 9 or above or Linux

Package Contents

- Passive Mini DisplayPort to DVI-I Adapter



