



## **USB-C to Dual DisplayPort Adapter - MST Hub**

**USB-C Male to Two DP Ports; Mirror, Extended and Video-Wall Modes Supported; 4K@30Hz; Black**

Part No.: [152952](#)

EAN-13: 0766623152952 | UPC: 766623152952

---

### **Easily distribute a single Ultra-High-Definition (UHD) signal to two displays.**

The Manhattan USB-C to Dual DisplayPort Adapter - MST Hub establishes a fast, simple and convenient link between a newer USB type-C-equipped media source (e.g., computer, tablet, smartphone, etc.) and up to two existing DisplayPort (DP) displays. Using DP Alt Mode technology, the adapter perfectly translates an audio/video signal from a single USB-C source into DisplayPort format (up to 4k@30Hz, UHD) and streams it simultaneously to one or two connected displays.

### **Flexible Solution for Many A/V Applications**

Ideal for trade shows, classrooms, video conferencing, presentations, office and retail applications, the Manhattan USB-C to Dual DisplayPort Adapter - MST Hub perfectly distributes a synchronous signal in either Mirrored or Extended modes to the connected displays. The included MST feature can create a video wall from the two displays, offering a more immersive experience whether in a gaming session, in a conference room or at the home office.

### **Quality Construction and Easy Installation**

Full compliance with DisplayPort, USB-C and HDCP standards ensures that the Manhattan USB-C to Dual DisplayPort Adapter - MST Hub can provide years of superior service and reliable performance. Setup is easy: simply connect the DP cables (not included) to the adapter and plug its USB-C connector into your device. That's all that's needed to complete this affordable, dual-UHD-display solution - no software/hardware configuration or complicated settings required.

## Features:

- Supports 4K@30Hz (Ultra-High-Definition, UHD) resolution, full 3D video and Deep Color
- Supports Mirror, Extended or Video-Wall modes
- Mirror mode duplicates the computer screen onto the connected displays
- Extended mode expands the desktop workspace onto the connected displays
- Video-wall mode uses two screens as one for a more immersive experience; requires a graphics card that supports Video-Wall function
- Mac OS X supports Mirror mode on up to two displays and Extended mode only on one display
- Plug and Play; requires no external power supply
- Three-year warranty

## Specifications:

### Standards and Certifications

- DP 1.2 over USB-C
- HDCP
- CE
- FCC
- RoHS2

### Connections

- One USB-C male (input)
- Two DisplayPort female (output)

### Signal Input/Output

- Input video signal: 0.5 – 1.0 V p-p
- Input DDC signal: 5 V p-p (TTL)
- Maximum single-link range: 5.4 Gbps, 3840x2160 at 30 Hz resolution
- Output video: HDCP

### Video Resolutions

- 480i/480p/576i/576p/720p/1080i/1080p/4K@30Hz

### Physical

- Cable Length: 195 mm (7.96 in.)
- Dimensions: 60 x 49 x 12 mm (2.36 x 1.93 x 0.47 in.)
- Weight: 49 g (1.8 oz.)
- Housing: plastic

### Operating Environment

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

#### System Requirements

- Windows XP/Vista/7/8.1/10
- Mac 10.12.4 or above
- DP 1.2 graphics card

#### Package Contents

- USB-C to Dual DisplayPort Adapter - MST Hub
- Quick Instruction Guide



