



# 4K@60Hz DisplayPort to HDMI Cable

DisplayPort Male to HDMI Male Cable, 1.8 m (6 ft.), Black

Part No.: 153201

EAN-13: 0766623153201 | UPC: 766623153201

# The easiest and best way to connect a DisplayPort laptop or desktop to your HDMI display — in one complete cable

For the simplest and most discreet installation, this DisplayPort to HDMI cable connects your DisplayPort video source to the HDMI port on your display. It doesn't need a power source, unlike some converter dongles that require active power and separate bulky video cabling. This cable lets you enjoy movies on a big-screen HDTV, extend your desktop to a second monitor (up to 4k@60Hz) for an expanded workspace, or show presentations on a projector at school or work without needing any other adapter or converter.

#### Features:

- Connects your DisplayPort source to your HDMI-equipped Ultra-HD display
- Supports Ultra-HD video resolution up to 4K@60Hz (3840 x 2160 at 60 Hz)
- Supports High-Definition audio for a full range of audio types, including SACD, DVD-Audio, DTS-HD Master Audio, and Dolby TrueHD

# manhattan® Life just got easier.™

### manhattan-products.com

- Supports 4:4:4 chroma subsampling
- Supports Ultra-HD video resolution up to 4K@60Hz (3840 x 2160 @ 60Hz) and High-Definition audio for a full range of audio types, including SACD, DVD-Audio, DTS-HD Master Audio, and Dolby TrueHD
- HDCP compatible for protected content
- Offers a latching DisplayPort connector to provide a secure connection
- Converts a signal from a DisplayPort source to an HDMI display only; not bi-directional
- Plug-and-Play
- Three-year warranty

#### **Specifications:**

#### Standards and Certifications

- DisplayPort v1.2
- FCC
- CE
- RoHS
- HDCP

#### General:

- Resolution: up to 3840 x 2160 at 60 Hz (Ultra-HD 4K@60Hz)
- Converts signal from DisplayPort to HDMI only
- 30 AWG

#### Connectors

- DisplayPort 20-pin male (latching)
- HDMI 19-pin male
- Gold-plated contacts

#### Physical

- Length: 1.8 m (6 ft)
- Weight: 110 g (3.9 oz.)
- Molded PVC and ABS Shell

#### Operating Environment

- Operation Temperature: 0 40°C (32 104°F)
- Storage Temperature: -20 60°C (-4 140°F)
- Humidity (noncondensing): 0 96%

#### System Requirements

• Windows XP/Vista/7/8.1/10, Linux or Mac 9.x/10.x or above

#### Package Contents

4K@60Hz DisplayPort to HDMI Cable



# manhattan-products.com











# manhattan-products.com

