



4K@60Hz Mini DisplayPort to HDMI Cable

Mini DisplayPort Male to HDMI Male Cable, 3 m (10 ft.), Black

Part No.: [153294](#)

EAN-13: 0766623153294 | UPC: 766623153294

One cable between a Mini DisplayPort source and an HDMI display — no adapter or converter required

For the simplest and most discreet installation, this Mini DisplayPort to HDMI cable connects your DisplayPort video source to the HDMI port on your display. It doesn't need a power source, unlike some converter dongles that require active power and separate bulky video cabling. This cable lets you enjoy movies on a big-screen HDTV, extend your desktop to a second monitor (up to 4K@60Hz) for an expanded workspace or show presentations on a projector at school or work without needing any other adapter or converter.

Features:

- Connects your Mini DisplayPort source to your HDMI-equipped Ultra-HD display
- Supports Ultra-HD video resolution up to 4K@60Hz (3840 x 2160 at 60 Hz)
- Supports High-Definition audio for a full range of audio types, including SACD, DVD-Audio, DTS-HD Master Audio, and Dolby TrueHD
- Supports Ultra-HD video resolution up to 4K@60Hz (3840 x 2160 @ 60Hz) and High-Definition audio for a full range of audio types, including SACD, DVD-Audio, DTS-HD Master Audio, and Dolby TrueHD
- HDCP compatible for protected content
- Converts a signal from a Mini DisplayPort source to an HDMI display only; not bi-directional

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Plug-and-Play
- Three-year warranty

Specifications:

Standards and Certifications

- DisplayPort v1.2
- FCC
- CE
- RoHS
- HDCP

General:

- Resolution: up to 3840 x 2160 at 60 Hz (Ultra-HD 4K@60Hz)
- Converts signal from Mini DisplayPort to HDMI only

Connectors

- Mini DisplayPort male
- HDMI 19-pin male
- Gold-plated contacts

Physical

- Length: 3 m (10 ft.)
- Weight: 120 g (4.2 oz.)
- Molded PVC and ABS Shell

Operating Environment

- Operation Temperature: 0 – 40°C (32 – 104°F)
- Storage Temperature: -20 – 60°C (-4 – 140°F)
- Humidity (noncondensing): 0 – 96%

System Requirements

- Windows XP/Vista/7/8.1/10, Linux or Mac 9.x/10.x or above

Package Contents

- 4K@60Hz Mini DisplayPort to HDMI Cable

