# manhattan-products.com





# **USB-C to 2.5GBASE-T Ethernet Adapter**

SuperSpeed USB 3.2 Gen 1; 10/100/1000 Mbps & 2.5 Gbps, Multi-Gigabit Ethernet, Black Part No.: 153300

EAN-13: 0766623153300 | UPC: 766623153300

## A USB-C to 2.5GBASE-T Ethernet Adapter for upgrading a computer or tablet to 2.5 Gbps speeds

## **USB-C Connectivity**

Since smaller laptops, notebooks and tablets omit the Ethernet port, you need an external adapter to get a wired Ethernet connection. This Ethernet Adapter delivers that at faster-than-gigabit speeds to help you enhance your productivity and move at the speed of business. The adapter's USB-C reversible connector lets you connect it right the first time, so you save time and avoid frustration or damage to your USB port. It's also the perfect replacement for your device's broken internal network card.

## **Fast and Frugal**

This 2.5G Ethernet Adapter has a fully auto-sensing Gigabit LAN port that is capable of delivering a peak performance of 5 Gbps in full-duplex mode. It delivers exceptional performance for everyone who requires an ultra-fast and solid network connection. The latest in power-saving technology ensures the adapter does not drain the battery of your computer in the process.

## **Portable Design**

This compact adapter takes up little space, so it can be added to your work area without adding clutter. You can add it to as many computers or tablets that you need. When it's time to leave one workspace, you unplug it and add it to your bag. When you're at the next, simply connect it and you're set with a super-fast wired-Ethernet connection.



#### **Features:**

- Adds a 2.5GBASE-T Ethernet port to any USB-C-enabled device
- IEEE 802.1Q VLAN tagging compliant
- IEEE 802.3az (Energy Efficient Ethernet) compliant
- IEEE 802.3bz 2.5GBASE-T compliant
- Supports jumbo frames up to 9K bytes
- Supports full-duplex operation with IEEE 802.3x flow control and halfduplex operation with back-pressure flow control
- USB 3.2 Gen 1 compliant (supports up to max 5 Gbps transfer rates)
- Thunderbolt 3 compatible
- Compatible with Cat5e or better cabling
- Supports Windows, Linux and Mac OS X
- Three-year warranty

#### Specifications:

Standards & Certifications

- CE
- RoHS
- FCC
- USB 3.2 Gen 1
- IEEE 802.1q (VLAN Tagging)
- IEEE 802.3bz (2.5GBase-T)
- IEEE 802.3az (Energy Efficient Ethernet)
- IEEE 802.3x (flow control)

#### General

- USB-C connector
- RJ45 port
- Cable length: 19.5 cm (7.67 in.)

#### Power

- USB bus-powered
- Operating mode: 420 mA
- Suspend mode: 38 mA

#### Physical

- Dimensions: 75 x 26 x 15 mm (2.95 x 1.02 x 0.59 in.)
- Weight: 34 g (0.07 oz.)

#### Environmental

- Operating temperature: 0 40°C (32 104°F)
- Storage temperature: -10 55°C (14 131°F)
- Storage humidity: 5 90%, non-condensing



### manhattan-products.com

System Requirements

- Windows 7, 8, 8.1, 10
- Mac OS 10.14.0, 10.14.1, 10.14.2
- Linux 3.2, 3.10, 3.12, 4.2, 4.4

Package Contents

- USB-C to 2.5GBASE-T Ethernet Adapter
- Quick Instruction Guide






For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com. All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.



### manhattan-products.com





For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com. All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.