



## USB-C to DisplayPort Converter with Power Delivery Port

4K@60Hz Resolution, Power Delivery up to 60 W (20 V / 3 A), Black  
Part No.: [153447](#)

EAN-13: 0766623153447 | UPC: 766623153447

### Our USB-C to DisplayPort Converter with Power Delivery (PD) Port: 4K DisplayPort signal from your device's USB-C port and power for all devices

The Manhattan USB-C to DisplayPort Converter with PD Port makes it easy to show content from your USB-C device on an existing DisplayPort display, monitor or projector. This converter is easy and quick to install — no settings or adjustments required. It is a compact yet powerful solution that helps avoid extra cables, tangles and clutter to keep workspaces neat and tidy.

### USB-C Power Delivery

The included USB-C PD port gives up to 60 W (20 V / 3 A) to all devices in your setup. Connecting the upstream device's cable and power adapter supplies power to the upstream device and boosts the 4K signal for a high-quality picture. The PD function also provides faster charging than standard chargers since it finds out the power needs of compatible devices and supplies it at the quickest and safest rate.

### Features:

- Supports resolutions up to 4K@60Hz following DisplayPort 1.2 standards
- Supports Power Delivery (PD) up to 60 W (20 V / 3 A)
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger - available from Manhattan

- Thunderbolt 3 compatible
- Compliant with DisplayPort 1.2 Alternate Mode (DP Alt Mode)
- Plug and play; requires no external power supply
- Fully shielded to reduce EMI and other interference sources
- Molded PVC boot and strain relief
- Lifetime warranty

## Specifications:

### Standards and Certifications

- USB 3.2 Gen 1
- DP 1.2 Alternate Mode
- PD 3.0
- DisplayPort 1.2
- HDCP 2.2
- CE
- FCC
- RoHS2
- WEEE

### Connections

- USB type C, 24-pin, male
- DisplayPort, 20-pin, female
- Power Delivery USB-C port

### Video Resolutions

- 4K@60Hz
- 4K@30Hz
- 2560 x 1600
- 2048 x 1280
- 1920 x 1200
- 1080p
- 720p
- 1024 x 768
- 800 x 600
- 640 x 480

### Physical

- 32-AWG cable gauge
- Mylar and aluminum shielding
- Thermal plastic casing
- Dimensions: 60 x 40 x 16 mm (2.36 x 1.57 x 0.63 in.)
- Cable length: 19.5 cm (7.67 in.)
- Weight: 31.76 g (1.12 oz.)
- Shielded
- Housing: ABS plastic

#### Operating Environment

- Operation Temperature: 0 - 50°C (32 - 122°F)
- Storage Temperature: -40 - 85°C (-40 - 185°F)
- Humidity (noncondensing): 0 - 96%

#### System Requirements

- Windows XP/Vista/7/8.1/10
- Mac 9.x/10.x or above
- Android

#### Package Contents

- USB-C to DisplayPort Converter with Power Delivery Port
- Instructions



