



3-Port USB 3.0 Type-C Hub with Power Delivery

USB-C Male to Three Type-A Ports Female and One Type-C Power-Delivery Port Female, 5 Gbps SuperSpeed USB (USB 3.2 Gen 1), 60 W via USB-C PD Port, White

Part No.: [163552](#)

EAN-13: 0766623163552 | UPC: 766623163552

Quickly connect more USB Type-A peripherals to Type-C devices

The Manhattan 3-Port USB 3.0 Type-C Hub with Power Delivery easily adds three SuperSpeed Type-A ports to any USB Type-C compatible device, expanding connectivity for keyboards, mice, external memory and other peripherals. Its SuperSpeed ports are backward compatible to support older devices. They provide data transfer speeds of up to 5 Gbps for external storage, printing and other activities, and they are capable of charging and powering at 5V/1A output. The Manhattan 3-Port USB 3.0 Hub with Power Delivery with Power Delivery can power the attached peripherals through the USB bus or by attaching the host device's charger to the Type-C port on the hub and power, which will charge the host device and connected peripherals.

Easy to add connectivity

A durable case, compact size and bus-power function make it easily transportable to add USB connectivity almost anywhere. Installation is simple with Plug and Play and hot-swappable capabilities. A built-in USB cable quickly connects the Manhattan 3-Port USB 3.0 Hub with Power Delivery to any USB Type-C port.

Features:

- Provides a Type-C device with three SuperSpeed USB Type-A ports for

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- additional peripherals
- USB-A ports support SuperSpeed (5 Gbps) data transmission, charging up to 5V/1A
- Bus powered / USB-C port charges host device and hub with USB Power Delivery (PD) using device's existing power supply
- Supports USB Power Delivery (PD) function up to 60 W; requires an external PD charger – available from Manhattan
- Overcurrent protection; hot-swappable
- Plug and play
- Three-Year Warranty

Specifications:

Standards and Certifications

- USB
- FCC
- CE
- RoHS2
- WEEE
- USB Power Delivery (PD) 2.0

General

- Data transfer speeds: 5 Gbps
- One upstream port with built-in cable, standard Type-C male
- Three downstream ports, standard Type-A female
- One downstream port, standard Type-C female
- Up to 1A total power output
- Bus powered
- Overcurrent protection

Connections

- USB Type-C, 24-pin, male
- Three USB Type-A, 4-pin, female
Output power 5V / 1A
- One USB Type-C, 24-pin, female
USB Power Delivery, no data transfer capabilities

Physical

- 24-AWG cable gauge
- Cable Length: 20 cm (8 in.)
- Withstanding voltage: 300 VDC
- Insulation resistance: 10 MOhm
- Conductive resistance: 5 Ohm
- Housing: ABS plastic
- Dimensions: 76 x 38 x 10 mm (3 x 1.5 x 0.4 in.)
- Weight: 31 g (1.1 oz.)
- Shielded

Operating Environment

- Operation Temperature: 0 - 40°C (32 - 104°F)
- Storage Temperature: -20 - 60°C (-4 - 140°F)
- Humidity (noncondensing): 5 - 90%

System Requirements

- Windows XP/Vista/7/8.1/10 or Linux or Mac 9.x/10.x or above

Package Contents

- 3-Port USB 3.0 Type-C Hub with Power Delivery
- Quick Instruction Guide



