



HDMI to DVI-D Cable

HDMI Male to DVI-D 24+1 Female, Dual Link, 20 cm (8 in.), Black

Part No.: [354592](#)

EAN-13: 0766623354592 | UPC: 766623354592

Superior connections for quality digital video performance

Manhattan HDMI to DVI Cables deliver the brightest, most accurate colors and sharpest detail when connecting high-definition televisions, LCD and plasma displays, digital satellite receivers, DVD players, digital projectors and other DVI- or HDMI-equipped display devices. Manhattan HDMI to DVI Cables are engineered and constructed of quality materials to deliver dependable transmissions in digital video applications. Full-foil and braided shielding, molded boots with strain relief, protective PVC jackets and gold-plated connections provide maximum conductivity and clear, crisp signal transmissions with reduced EMI interference and distortion.

Features:

- HDMI 19-pin male to DVI-D 24+1 female; gold-plated connections
- Connects HDMI video source and DVI-D display
- Fully shielded to reduce EMI and other interference sources
- Supports existing HD (720p, 1080i and 1080p@60Hz), enhanced (480p) and standard (NTSC or PAL) video formats
- Molded PVC boot
- Lifetime warranty

Specifications:

Standards and Certifications

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Meets or exceeds existing HDMI and DVI-D standards
- Compatible with DVI-D dual link devices
- UL
- ISO

Connections

- One HDMI 19-pin male
- One DVI-D 24+1-pin female
- Molded PVC boot
- Shielded
- 28 AWG connectors

Cable

- Shielded
- Length: 20 cm (8 in)
- Current rating: 0.5 A DC
- Withstanding voltage: 300 V DC
- Insulation resistance: 10 MOhms
- Conductive resistance: 1 Ohm
- Thermal plastic casing

Operating Environment

- Operation Temperature: 0 - 40°C (32 - 104°F)
- Storage Temperature: -20 - 60°C (-4 - 140°F)
- Humidity (noncondensing): 5 - 90%

Package Contents

- HDMI to DVI-D Cable



