



USB 3.2 Gen 2 Type-C Device Cable

USB-C Male to USB-C Male, 0.5 m (1.5 ft.), SuperSpeed+ USB, 10 Gbps, 60 W / 3 A, 4K@60Hz, Black

Part No.: [354899](#)

EAN-13: 0766623354899 | UPC: 766623354899

Manhattan SuperSpeed USB Type-C Cables easily connect USB Type-C peripherals and accessories to Type-C device ports. Ideal for use with any USB-C plug-and-play device, these cables support data transfer rates of up to 10 Gbps on Windows and Mac systems for fast, reliable transmissions and current of up to 3 amps. Nickel-plated contacts, shielding and fully molded boots with strain relief provide dependable connections, maximum conductivity and minimal data loss with reduced EMI interference.

Features:

- USB-C male to USB-C male
- Connects a USB 3.2 Gen 2 SuperSpeed type-C device to a SuperSpeed type-C port
- Supports speeds of up to 10 Gbps
- Supports current of up to 3 A (60 W)
- USB-C compliance with DisplayPort 1.2 Alternate Mode (DP Alt Mode) for resolutions up to 4K@60Hz on supported devices and displays
- SuperSpeed USB for ultra-fast data transfer rates and zero data degradation
- Lifetime Warranty

Specifications:

Standards and Certifications

- UL 2725
- USB 3.2 Gen 2 (10 Gbps)

For more information on Manhattan products, consult your local dealer or visit www.manhattan-products.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Connectors

- Two USB-C males
- Nickel plated
- Molded PVC boot

Cable

- Shielded
- Withstanding voltage: 300 VDC 10 ms
- Insulation resistance: 10 MOhm
- Conduction resistance: 2 Ohm
- Thermal plastic casing

Operating Environment

- Operation temperature: 0 - 50°C (32 - 122°F)
- Storage temperature: -20 - 80°C (-4 - 176°F)

Package Contents

- USB 3.2 Gen 2 Cable



