



Industrial 8-Port Gigabit Ethernet Switch with 2 SFP Ports

IP40-Rated Metal Housing, DIN-Rail Mount

Part No.: **508827**

EAN-13: 0766623508827 | UPC: 766623508827

Industrial Ethernet Switch with Gigabit connectivity for harsh industry environments

The Industrial 8-Port Gigabit Ethernet Switch with 2 SFP Ports from Intellinet Network Solutions was designed to give you the network connections you need in places that are less than calm or temperate. With its rugged, IP40-rated metal housing, it operates reliably and quietly, even under extreme temperatures that range from -40 to 75°C (-40 to 167°F). In combination with its DIN-rail mounting option and two safe redundant DC power inputs with power failure alarm and plenty of other safety features, this switch is ideal for IoT applications in Industry 4.0 and more. Featuring eight auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, this unmanaged switch offers plenty of performance for the devices in your network. In addition, two small form-factor pluggable GBIC module slots (SFP) provide fiber connectivity for greater distances.

Features:

- 10/100/1000 auto-sensing ports that automatically detect optimal network speeds
- IP40 slim-type metal housing to withstand harsh industrial conditions
- Suitable for extreme operating temperatures of -40 to 75°C (-40 to 167°F)
- Option for DIN-rail installation
- Two small form-factor pluggable GBIC module slots (SFP)
- Two redundant DC inputs (12 - 48 V) with I/O terminal block
- Power failure alarm (one-way relay output, current load capacity 1 A @ 24 V DC)

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Port surge protection up to 6 kV
- Grounding point to protect equipment from external electrical surges
- Rated for shock (IEC 60068-2-27), freefall (IEC 60068-2-32) and vibration (IEC 60068-2-6)
- 20 Gbps switch fabric
- Auto-MDIX and NWay auto-negotiation support on all RJ45 ports
- Provides IEEE 802.1x port-based security
- Supports 4k MAC address entries with Auto-Learning and Auto-Aging
- Buffer memory of 1.75 Mbits
- Supports jumbo frames up to 9.6 KB
- Store and forward switching architecture
- Full/half duplex operation
- IEEE 802.3x flow control for full duplex
- LEDs for power, link/activity, and SFP
- Requires additional industrial power supply (not included)
- Fully NDAA-compliant
- Three-year warranty

Specifications:

Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted pair Gigabit Ethernet)
- IEEE 802.3i (Twisted pair 10Base-T Fast Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (Flow control for full-duplex mode)
- IEEE 802.3z (1000BASE-X Gigabit Ethernet)

General

- Media support:
 - 10Base-T Cat3/4/5 UTP/STP RJ45, 8 pin
 - 100Base-TX Cat5/5e UTP/STP RJ45, 8 pin
 - 1000Base-T Cat5e/6/6a UTP/STP RJ45, 8 pin
- Packet filter/forwarding rate:
 - 1,488,000 pps (1000 Mbps)
 - 148,800 pps (100 Mbps)
 - 14,880 pps (10 Mbps)
- MAC address table: 4k entries
- Buffer memory: 1.75 Mbits
- Backplane speed / switching capacity: 20 Gbps
- Switch architecture: store and forward
- Certifications: FCC Class A, CE, UKCA, NDAA

LEDs

- Power
- Link/activity
- SFP

Power

- Input voltage: 12.0 - 48.0 VDC
- Power consumption: 7.44 watts (max.)

Physical

- Metal housing
- DIN-rail: In accordance with IEC/EN 60715 (top hat)
- Dimensions (L x W x H): 100 x 190 x 28 mm (3.94 x 7.48 x 1.1 in.)
- Net weight: 700 g (1.54 lbs.)
- Gross weight: 1 kg (2.2 lbs.)
- Operating temperature: -40 - 75°C (-40 - 167°F)
- Storage temperature: -40 - 85°C (-40 - 185°F)
- Operating humidity: 5 - 95% RH, non-condensing
- Storage humidity: 5 - 95% RH, non-condensing

Package Contents

- Industrial 8-Port Gigabit Ethernet Switch with 2 SFP Ports
- DIN-rail mount bracket
- Instructions



