



## Industrial Gigabit PoE++ Splitter

IEEE 802.3bt (4PPoE) Compliant, up to 60 W Input, 12 V / 4.25 A DC Output, IP30-rated Metal Housing, DIN-rail Mount

Part No.: 508940

EAN-13: 0766623508940 | UPC: 766623508940

### Turn a higher-power PoE link into separate DC/terminal-block power and Gigabit data connections

Need power but don't have an outlet? Take it from your PoE network with the Intellinet Industrial Gigabit PoE++ Splitter. With a simple Ethernet cable connected to your PoE++ Switch or injector, this Splitter can give up to 51 W to a non-PoE device in tough or industrial environments via your choice of output — a 2-pin terminal block or a DC jack — and still provide a gigabit network connection. It's a great choice for non-PoE cameras, laptops, and other devices that require a power adapter, and it's cheaper in both time and money than hiring an electrician.

#### Features:

- Splits an IEEE 802.3bt PoE++ connection into power and Gigabit Ethernet for non-PoE devices
- Two DC outputs with power up to 12 V / 4.25 A / 51 W via 2-pin terminal block or DC jack
- One RJ45 input port up to 60 W from an IEEE 802.3bt/at/af-compliant PoE injector or PoE switch (PSE)
- One RJ45 output port with 10/100/1000 data rates
- IP30-rated metal housing to withstand harsh industrial conditions
- Suitable for extreme operating temperatures of -40 to 75°C (-40 to 167°F)
- Option for DIN-rail installation
- Distance support: up to 100 m (328 ft.)

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Short-circuit, overload and high-voltage protection
- Grounding point to protect equipment from external electrical surges
- ESD protection up to 8 kV (air) and 6 kV (contact)
- Port surge protection up to 2 kV
- Fully NDAA-compliant
- Three-year warranty

## Specifications:

### Standards

- IEEE 802.3af (Power over Ethernet)
- IEEE 802.3at (High-Power PoE+ Power over Ethernet)
- IEEE 802.3bt (PoE++/4PPoE Power over Ethernet)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3ab (1000BASE-T Gigabit Ethernet)

### General

- Media support:
  - 10Base-T Cat5e/6/6a UTP/STP RJ45
  - 100Base-TX Cat5e/6/6a UTP/STP RJ45
  - 1000Base-T Cat5e/6/6a UTP/STP RJ45
- Ports:
  - One RJ45 10/100/1000 Mbps PoE input port
  - One RJ45 10/100/1000 Mbps data output port
  - One DC output port
  - One DC output with 2-pin terminal block
- Certifications: FCC Class A, CE, RoHS, UKCA, NDAA

### Power

- Input power: IEEE 802.3bt/at/af compliant PSE, 60.0 W max., 36.0 - 57.0 V DC
- Max. output power: 51.0 W, 12.0 V DC, 4.25 A
- Power consumption: 60.0 W (max.)

### PoE Pinout

- Pin 1: DC (+)
- Pin 2: DC (+)
- Pin 3: DC (-)
- Pin 4: DC (+)
- Pin 5: DC (+)
- Pin 6: DC (-)
- Pin 7: DC (-)
- Pin 8: DC (-)

### LED

- Power

## Physical

- IP30-rated metal housing
- DIN-rail: In accordance with IEC/EN 60715 (top hat)
- Dimensions (L x W x H): 103 x 78 x 32 mm (4.06 x 3.07 x 1.26 in.)
- Net weight: 330 g (0.73 lbs.)
- Gross weight: 382 g (0.84 lbs.)
- Operating temperature: -40 - 75°C (-40 - 167°F)
- Storage temperature: -40 - 85°C (-40 - 185°F)
- Operating humidity: 5 - 95% RH, non-condensing
- Storage humidity: 5 - 95% RH, non-condensing
- Recommended AWG for terminal block: 12 - 24

## Package Contents

- Industrial Gigabit PoE++ Splitter
- DIN-rail mount bracket
- Instructions



