



8-Port Gigabit Ethernet PoE+ Web-Managed AV Switch with 2 SFP Uplinks

Eight Rear-Facing PoE+ ports, IEEE 802.3at Power over Ethernet (PoE+), Layer2+, Two 1 GbE SFP Open Slots, Endspan, 19" Rackmount

Part No.: **561433**

EAN-13: 0766623561433 | UPC: 766623561433

The Intellinet Solutions 8-Port Gigabit Ethernet PoE+ Web-Managed AV Switch with 2 SFP Uplinks is an enterprise-class switch specifically designed for use in AV rack applications. With front-facing indicators and rear-facing ports, the switch is designed for easy installation and high performance in an environment where traffic on the network and the number of users could increase continuously.

* Total PoE budget for this switch is 255 watts. Maximum per-port power usage cannot exceed 30 watts.

Features:

- Rear-facing IEEE 802.3at/af-compliant RJ45 PoE/PoE+ Gigabit Ethernet ports
- Provides power and data connection for up to eight PoE network devices
- Domotz compatible for cloud management (may require firmware upgrade)
- 10/100/1000 auto-sensing ports for automatic detection of optimal network speeds
- Two small form-factor pluggable 1 GbE SFP module slots
- Console port for configuring
- Power output up to 30 watts per port*
- PoE power budget of 255 watts
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (e.g., wireless access points, VoIP phones, IP cameras, etc.)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- Management by Web/SNMP/Telnet/Console
- All RJ45 ports with Auto-MDIX and NWay auto-negotiation support
- Complies with the IEEE 802.3az (Energy Efficient Ethernet EEE) specification
- 20 Gbps switch fabric

- SNMP Management and Remote Monitoring (RMON)
- Remote reboot/restart
- The Powered Device Monitor feature (PDM) restarts any connected PoE device that fails to respond or send out network traffic.
- IPv4/v6 dual protocol
- Supports VLAN (tag-based and port-based)
- Provides IEEE 802.1x port-based security
- Supports link aggregation (trunking)
- Supports bandwidth control per port
- Supports port mirroring
- Supports two types of QoS: port-based and DSCP
- Broadcast storm control with multicast packet-rate settings
- Supports Spanning Tree Protocol (STP) IEEE 802.1d
- Store and forward switching architecture
- IEEE802.3x Flow Control
- Supports jumbo frames up to 10 kBytes
- Supports 8k MAC address entries
- LEDs for power, link/activity and PoE
- Includes 19" rackmount brackets
- Includes console cable
- Three-year warranty

Specifications:

Standards

- IEEE 802.1d (Spanning Tree Protocol [STP])
- IEEE 802.1p (Traffic Prioritization)
- IEEE 802.1q (VLAN Tagging)
- IEEE 802.1s (Multiple Spanning Tree Protocol [MSTP])
- IEEE 802.1w (Rapid Spanning Tree Protocol [RSTP])
- IEEE 802.3ad (Link Aggregation)
- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted Pair Gigabit Ethernet)
- IEEE 802.3ad (Link Aggregation Control Protocol [LACP])
- IEEE 802.3az (Energy Efficient Ethernet [EEE])
- IEEE 802.3af (Power over Ethernet 802.3at Type 1)
- IEEE 802.3at (Power over Ethernet 802.3at Type 2)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (Flow Control for full duplex mode)

General

- Media support:
 - 10Base-T UTP/STP RJ45
 - 100Base-TX UTP/STP RJ45
 - 1000Base-T UTP/STP RJ45
- MAC address table: 8k
- Backplane speed / switch fabric: 20 Gbps

- Buffer Memory: 4.1 MB
- Forwarding Rate: 14.88 Mpps
- Switch architecture: store and forward
- Configuration options:
 - Port link speed: 10 Mbps, 100 Mbps, 1000 Mbps or auto-negotiation
 - PoE on/off per port
 - Flow Control on/off per port
 - VLAN
 - Rate limiting (ingress rate and egress rate)
 - Port Mirroring, one to one or many to one
 - Port Aggregation/LACP: 8 groups
 - Broadcast Storm configuration with broadcast rate, multicast rate and flooded unicast rate
 - IGMP Snooping
 - Access management filtering: SNMP, HTTP, HTTPS, SSH, Telnet
 - Quality of Service (QoS): port-based or DSCP
 - Link Layer Discovery Protocol (LLDP) - Station and Media Access Control Connectivity Discovery
 - LLDP-MED Extension (TIA specific TLVs)
 - Integrated ICMP Ping client sends ping requests to other network nodes
 - SNMPv1/v2c/v3 (Simple Network Management Protocol)
 - RMON
 - DHCP: Server/Client
 - LAN settings (IP address, Gateway, etc.)
 - EEE Energy Efficient Ethernet
 - SSHv2
- Certifications: FCC Class B, CE

LEDs

- PoE
- Power
- Link/activity

Power

- Input: 100 – 240 VAC, 50 – 60 Hz
- Power consumption: 270 watts (maximum)

Environmental

- Metal housing
- Dimensions: 200 (L) x 440 (W) x 44 (H) [mm] / 7.87 (L) x 17.32 (W) x 1.73 (H) [in.]
- Weight: 3.2 kg (7.05 lb.)
- Operating temperature: 0 – 40°C (32 – 104°F)
- Operating humidity: 20 – 85% RH, non-condensing
- Storage temperature: -10 – 70°C (14 – 158°F)

Package Contents

- 8-Port Gigabit Ethernet PoE+ Web-Managed AV Switch with 2 SFP Uplinks

- Power cable
- User manual
- 19" rackmount brackets
- Console cable
- Four rubber feet

