



5-Port Gigabit Ethernet PoE+ Switch with SFP Port

Four PSE PoE Ports, IEEE 802.3at/af (PoE+/PoE) Compliant, PoE Power Budget of 91 W, Desktop Format, Wall-mount Option

Part No.: **561822**

EAN-13: 0766623561822 | UPC: 766623561822

Desktop 5-Port PoE Switch with Gigabit Uplinks - Supports 10/100/1000 Mbps, Power over Ethernet 802.3at

The 5-Port Gigabit Ethernet PoE+ Switch with SFP Port from Intellinet Network Solutions passes both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with five Gigabit Ethernet ports - four of which are high-power PoE+ PSE ports - this switch can power wireless LAN access points and bridges, VoIP phones, IP video cameras and more while delivering network speeds of up to 1000 Mbps.

High-power PoE+ with output up to 30 watts

This switch supports the IEEE 802.3at protocol and can inject up to 30 watts of power per port. IEEE802.3af- or IEEE802.3at-compliant devices attached to the switch require no additional power, which eliminates the time and expense of electrical rewiring and minimizes the unsightly clutter caused by power supplies and adapters in awkward places such as ceilings and walls. Any mix of PoE and non-PoE devices is supported, and thanks to its short circuit, overload and high-voltage protection function, your equipment is well-protected.

Gigabit Uplinks

The switch is equipped with one Gigabit RJ45 and one SFP transceiver module slot. These Gigabit uplink ports are ideal for connecting the switch to the network's backbone, a server or, perhaps, your video recording solution (NVR).

Wall-mount option

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

For full installation flexibility, you can mount the switch on the wall through its four built-in holes or use the included non-slip rubber feet to place it on a desktop.

Features:

- Provides up to four PoE network devices with power and data
- Four 10/100/1000 Mbps IEEE 802.3at/af-compliant RJ45 PoE ports, one gigabit RJ45 port and one gigabit SFP port
- PoE power budget of 91 watts
- Power output up to 30 watts per port
- Saves installation costs by delivering data and power over existing network cables
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (e.g., wireless access points, VoIP phones, IP cameras)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- 12 Gbps switch fabric
- 10/100/1000 auto-sensing ports that automatically detect optimal network speeds
- Auto-MDIX and NWay auto-negotiation support on all RJ45 ports
- Store and forward switching architecture
- IEEE 802.3x flow control for full duplex
- Supports 2k MAC address entries
- Compact desktop format with rugged metal housing
- Grounding point to protect equipment from external electrical surges
- Mounting holes for wall mounting
- Rubber feet for non-slip desktop use
- Fanless design ideal for silent operation
- Fully NDAA-compliant
- Three-year warranty

Specifications:

Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted Pair Gigabit Ethernet)
- IEEE 802.3af (Power over Ethernet 802.3at Type 1)
- IEEE 802.3at (Power over Ethernet 802.3at Type 2)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- IEEE 802.3x (flow control, for full duplex mode)

General

- Media support:
 - 10Base-T Cat5e UTP/STP RJ45, 8 pin

- 100Base-TX Cat5e UTP/STP RJ45, 8 pin
- 1000Base-T Cat5e UTP/STP RJ45, 8 pin
- Forwarding rate: 8.928 Mpps
- Backplane speed / switch fabric: 12 Gbps
- Switch architecture: store and forward
- Certifications: FCC Class A, CE, RoHS, UKCA, NDA

LEDs

- Power
- Link/activity
- PoE

Pinout RJ45 output ports, mode A

- Pin 1: DC (+)
- Pin 2: DC (+)
- Pin 3: DC (-)
- Pin 6: DC (-)

Power

- Included power adapter:
 - Input: 100.0 - 240.0 VAC, 50 - 60 Hz, 2.5 A
 - Output: DC, 48.0 V, 2.0 A
 - PoE budget: 91.0 watts (maximum)
 - Power consumption: 96.0 watts (maximum)

Physical

- Metal housing
- Dimensions (L x W x H): 86 x 153 x 29 mm (3.39 x 6.02 x 1.14 in.)
- Net weight: 800 g (1.76 lbs.)
- Gross weight: 925 g (2.04 lbs.)
- Operating temperature: 0 - 40°C (32 - 104°F)
- Storage temperature: -10 - 70°C (14 - 158°F)
- Operating humidity: 20 - 85% RH, non-condensing
- Storage humidity: 5 - 90% RH, non-condensing

Package Contents

- 5-Port Gigabit Ethernet PoE+ Switch with SFP Port
- Power adapter
- Power cable
- Four rubber feet
- Instructions

