



## 24-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports

IEEE 802.3at/af (PoE+/PoE) Compliant, PoE Power Budget of 370 W, Two 1G SFP Open Slots, 19" Rackmount

Part No.: **561891**

EAN-13: 0766623561891 | UPC: 766623561891

---

## Unmanaged PoE Switch with 26 ports - 24 RJ45 and Two SFP, High-Power PoE+

The Intellinet Network Solutions 24-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports passes both data and electrical power to a number of PoE-compatible devices via standard Cat5e or Cat6 network cables. Equipped with 24 Gigabit Ethernet ports, this switch can power wireless LAN access points and bridges, VoIP phones, IP video cameras and more while delivering network speeds up to 1,000 Mbps.

### Power over Ethernet 802.3at

This high-powered switch supports the IEEE 802.3at protocol and can inject up to 30 watts of power per port. IEEE802.3af- or IEEE802.3at-compliant devices attached to the switch need no additional power to help avoid the time and expense of electrical rewiring and minimize the unsightly clutter of power supplies and adapters on ceilings and walls. Any mix of PoE and non-PoE devices is supported, and thanks to its short-circuit, overload and high-voltage protection function, your equipment is well-protected. For devices that are not 802.3at/af compliant (legacy wireless access points or network cameras), we suggest the use of an Intellinet Network Solutions PoE/PoE+ Splitter.

### Eliminate Bottlenecks with 26 Gigabit Ports

Equipped with 24 auto-sensing 10/100/1000 Mbps RJ45 Gigabit Ethernet ports, this switch offers plenty of performance for your computers, servers and other networking devices. In addition, two small form-factor pluggable (SFP) GBIC module slots provide fiber connectivity for greater distances. These are not shared combo-ports but true Gigabit ports, pushing the total available bandwidth up to 52 Gbps.

## Features:

- Provides up to 24 PoE network devices with power and data
- Two 1G small form-factor pluggable (SFP) module slots
- PoE power budget of 370 watts
- Power output up to 30 watts per port
- Manual VLAN mode to isolate ports 1 to 24 from each other while allowing them to communicate with SFP uplink ports 25 and 26
- Manual Flow Control Off mode to disable the Gigabit Ethernet switch's flow-control function
- 52 Gbps switch fabric
- 10/100/1000 auto-sensing ports that automatically detect optimal network speeds
- Complies with the IEEE 802.3az (Energy Efficient Ethernet EEE) specification
- Green Ethernet power-saving technology that deactivates unused ports and adjusts power levels based on the cable length
- Saves installation costs by delivering data and power over existing network cables
- Supports IEEE 802.3at and IEEE 802.3af-compliant PoE devices (e.g., wireless access points, VoIP phones, IP cameras)
- Supports IEEE 802.3at/af detection and short circuit, overload and high-voltage protection
- Auto-MDIX and NWay auto-negotiation support on all RJ45 ports
- Supports jumbo frames up to 9.2 kBytes
- All RJ45 ports with Auto-MDIX (auto uplink) support
- Store and forward switching architecture
- Supports 802.3x flow control for full duplex mode and collision-based backpressure for half duplex mode
- Supports 8k MAC address entries with Auto-learning and Auto-aging
- 512 kBytes buffer memory
- Two high-volume cooling fans to ensure perfect ventilation
- Includes 19" rackmount brackets
- Fully NDAA-compliant
- Three-year warranty

## Specifications:

### Standards

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3ab (Twisted Pair Gigabit Ethernet)
- IEEE 802.3az (Energy Efficient Ethernet EEE)
- IEEE 802.3af (Power over Ethernet 802.3at Type 1)
- IEEE 802.3at (Power over Ethernet 802.3at Type 2)
- IEEE 802.3u (100Base-TX Fast Ethernet)

For more information on Intellinet products, consult your local dealer or visit [www.intellinet-network.com](http://www.intellinet-network.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- IEEE 802.3x (flow control for full duplex mode)

#### General

- Media support:
  - 10Base-T Cat5e UTP/STP RJ45, 8 pin
  - 100Base-TX Cat5e UTP/STP RJ45, 8 pin
  - 1000Base-T Cat5e UTP/STP RJ45, 8 pin
- MAC address table: 8k
- Buffer memory: 512 kBytes
- Forwarding rate: 36.688 Mpps
- Backplane speed / switch fabric: 52 Gbps
- Switch architecture: store and forward
- Certifications: FCC, CE, RoHS, UKCA, NDAA

#### LEDs

- Power
- Link/activity
- PoE

#### Pinout RJ45 output ports

- Pin 1: DC (+)
- Pin 2: DC (+)
- Pin 3: DC (-)
- Pin 6: DC (-)

#### Power

- Input: 100.0 - 240.0 VAC, 50 - 60 Hz, internal power supply
- Power consumption: 400.0 W (max.)

#### Physical

- Metal housing
- Dimensions (L x W x H): 208 x 440 x 44 mm (8.19 x 17.32 x 1.73 in.)
- Net weight: 3.37 kg (7.43 lbs.)
- Gross weight: 3.87 kg (8.53 lbs.)
- Operating temperature: 0 - 45°C (32 - 113°F)
- Storage temperature: -40 - 70°C (-4 - 194°F)
- Operating humidity: 10 - 90% RH, non-condensing
- Storage humidity: 5 - 90% RH, non-condensing

#### Package Contents

- 24-Port Gigabit Ethernet PoE+ Switch with 2 SFP Ports
- Power cable
- Instructions
- 19" rackmount brackets



EU or US Plug