



Breakaway groove facilitates threading ring into a smaller opening.

Plastic mounting ring for recessed installation of an 8" speaker with a screw-mount grille in a new or retrofit ceiling or wall is an economical alternative to using a recessed backbox where not required by specifications or code.

Note that speaker installation should always be performed according to all local building codes and regulations, many of which require a backbox.

FEATURES:

- **Construction:** Flexible plastic ring with U-nuts
- **Diameter:** 13.812" dia. A breakaway groove facilitates threading the ring into a smaller opening (12.125" dia.)
- **Installation:**
 - **Breakaway Groove:** Snap the breakaway groove and thread the 13.812" dia. ring into a pre-cut 12.125" hole. The ring can be held in place and anchored using flush head screws.
 - **Anchor Holes:** Locating anchor holes in retrofit and room-side installations can be tricky. Prior to threading the ring through the ceiling, notice the eight outer anchor holes are positioned 1.375" out from grille mounting holes. When the ring is installed, grille mounting holes are visible and the anchor holes can be located by measuring 1.375" out from the grille holes.
- **Origin:** Made in the U.S.A.
- **A&E Specifications:** The mounting ring shall be Lowell model RMP8, which shall screw-mount an 8" speaker with Lowell grille model _____. The mounting ring shall be of flexible plastic construction with a breakaway groove that allows the ring to install in a 12.125" dia. opening. The ring shall have a 13.812" dia. and thickness of 0.375". It shall be equipped with 8-32 screw retaining clips. The outer rim shall have an additional eight mounting holes for application needs.

COMPATIBLE COMPONENTS:

- Speaker: Standard 8" speaker
- Screw-Mount Grille: A8-AW, CS-8H, L08-P, RS8-AW, WB-8, WB-8H



Model Summary

Model No.	Description	Material	Color	Diameter*	Origin
RMP8	Mounting Ring	Plastic	Black	13.812"	U.S.A.

**Breakaway groove facilitates fitting the ring into a smaller opening*



