



## Product information sheet

# AXADBXH-CH3 Chrysler Data Interface 2013-Up\*

\*Visit [AxxessInterfaces.com](http://AxxessInterfaces.com) for up-to-date vehicle specific applications.

## INTRODUCTION

The AXADBXH-CH3 harness is designed for, and must be used with, the AXADBX-1 or AXADBX-2 interface (sold separately). Please refer to the AXADBX-1 or AXADBX-2 for the 16-pin connector with stripped leads.

## INTERFACE FEATURES

- Provides accessory power (12-volt 10-amp)
- Maintains the retained accessory power (R.A.P.) feature
- Can be used in non-amplified, or amplified models
- Provides NAV outputs (parking brake, reverse, speed sense)
- Pre-wired AXSWC harness (AXSWC sold separately)
- Retains the factory backup camera†
- Retains the factory AUX-IN jack
- Retains balance and fade\*
- Micro "B" USB updatable

† Only if the camera is displayed on the factory radio

\* To retain fade in amplified models, use the AXADBX-1

## INTERFACE COMPONENTS

- AXADBXH-CH3 harness

## APPLICATIONS

### CHRYSLER

200 LX 2015-2016

### DODGE

Dart  
(small screen option) 2013-2016

### JEEP

Cherokee (Sport trim) 2014-2017

Compass (Sport trim) 2017.5-Up

### RAM

1500/2500/3500

(small screen option) 2013-2017

Chassis Cab 3500, 4500, 5500

(small screen option) 2013-2017