

AXDSPX-ETH1 INTERFACE



INTERFACE COMPONENTS

- AXDSPX-ETH1 interface
- AXDSPX-FTH1 harness
- ID-DSP-FTH1
- LD-DSP-ETH2
- AXBK-1
- AXDSPX-ETH1 interface harness (male connectors: 8-pin, 16-pin)
- Amplifier bypass harness (female connectors: 8-pin black and 20-pin green)

GENERAL MOTORS 2019-Up **ETHERNET DSPX PACKAGE**

Visit **axxessinterfaces.com** for current application list.

Visit <u>AxxessInterfaces.com</u> for more detailed information about the product and up-to-date vehicle specific applications.

INTERFACE FEATURES

- Designed for GM Ethernet amplifiers
- Ethernet data interface w/AXDSP-X (digital signal processor) built-in
- Includes an amplifier bypass harness
- Retains factory chimes including parking sensor chimes
- Retains vehicle's voice prompts
- Chimes and voice prompts go through the aftermarket amplifier and/or cluster
- Selectable 31 Band graphic EQ or 5 Band Parametric EQ
- 10 individually assignable outputs

- Independent equalization on each of the 10 outputs
- Independent high pass, low pass, and bandpass filters
- Each channel can be delayed independently up to 10ms
- Clipping detection and limiting circuits
- Settings adjusted via Bluetooth® in a smart device application (tablet or mobile phone), compatible with both Android and Apple devices
- Read, write, and store configurations for future recall
- Password protect feature available in the mobile app
- Micro-B USB updatable

SALES 386-257-2956

REV. 8/19/22