

SKU # 9006LEDDSv2

Part # 1007435

Description

V2 DRIVE Series 9006 2,500 LUX Driverless Plug-&-Play LED Headlight Kit w/ Canbus Decoder 3yr warranty

Categories LED Headlight Conversions

Sub-Categories DRIVE Series V2 CANBUS

UPC 817999029857

Unit of Measure Kit

Related Skus:

Cross Sell Skus:

RSIKIT, RSUKIT, RS8PRGBW

Condition

New

Manufacturer

Race Sport Lighting

Operating Voltage

EZ Category

V2 Drive Series CANBUS

Kits

Harmonization Code

8512.20.2080

Universal

YES

12VDC

Life Expectancy

50,000 hours

SEMA Product

Headlight Conversion Kit

Part Type ID 12571

Reverse Polarity Headlight Conversion Kit

Current Draw

Wattage

Chip Type **PHILLIPS**

IP Rating

IP67

LUX

5.960 RAW LUX

Kelvin (ColorTemperature)

6,000K

Made In CN

Warranty 3 year

Universal or Vehicle Specific

Universal

Lumens 4,960 RAW LUMEN

Beam Pattern

Directional

Prop 65 WARNING: This product can expose you to chemicals, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov



Product Information

Est. Labor

DIM Weight

The NEW V2 DRIVE Series is the latest LED headlight and foglight kit in the industry for ATV's, Motorcycles, Race bikes, Off-Road vehicles, and Automotive. All the solutions for LED's have been built into this technology. The LED kit does not contain a driver, but does come with an optional Canbus Decoder pack to plug n play between the LED bulbs and the vehicle to steady voltage, and interface with CANBUS functional vehicles. The size of the bulb bases are specifically designed to eliminate fitment issues from oversized aftermarket bulbs. The light output and performance is amazing at 2,500 LUX, and great for night time safety driving. General Specs: -Rated LUX output -2,500 LUX/bulb or 5,000 LUX/kit -RAW LUX light output is 2,980lx/bulb or 5,960lx/kit -RAW Lumen Measured on Meter is 2,480lm/bulb or 4,960lm/kit Warranty - 3yr Warranty Canbus - Canbus Decoders included in kits -Plug N Play OEM sized (no fitment issues) -Temperature: -45±85 °C -Voltage: DC9V-32V -Beam Angle:330° -6,

Gross Weight	1.90	Width	7.50
Net Weight	1.00	Height	2.50

0.74

0.5 Hours

www.racesportinc.com

Depth

5.50