



# SONANCE

## SONANCE SS4VC SPEAKER SELECTOR WITH VOLUME CONTROL (EACH)

Controls up to 4 sets of speakers. Features a soft touch rotary volume control and advanced overload protection. Quick connectors on the rear panel make for quick installation.

### Dimensions (WxHxD):

16 7/8" x 2 3/16" x 10 1/4" (429mm x 56mm x 260mm)

### RMF Dimensions (WxHxD):

19" x 1 3/4" x 10 1/4" (483mm x 45mm x 260mm)



### Power Rating:

75 watts RMS maximum input per channel

### Volume Control:

12 position light touch silent rotary switch

### Frequency Response:

20-20kHz  $\pm$ 1dB

### Connections:

Toggle quick disconnect 20-14 AWG wire capacity

### Speaker Impedance:

8 ohms per zone

### Total Atenua on:

-42dB: full clockwise position is straight through; full counterclockwise position is "off"

### Atenua on Steps:

Top seven steps are -3dB per step; lowest four steps are -6dB per step. **Included Accessories:**

Removable rack ears

Specifications	
Power Rating	75 watts RMS maximum input per channel
Volume Control	12 position light touch silent rotary switch
Connections	Toggle quick disconnect 20-14 AWG wire capacity
Frequency Response	20-20kHz $\pm$ 1dB
Speaker Impedance	8 ohms per zone
Total Attenuation	-42dB: full clockwise position is straight through; full counterclockwise position is "off"
Attenuation Steps	Top seven steps are -3dB per step; lowest four steps are -6dB per step.
Included Accessories	Includes removable rack ears
Dimensions (WxHxD)	16 7/8" x 2 3/16" x 10 1/4" (429mm x 56mm x 260mm)
RMF Dimensions (WxHxD)	19" x 1 3/4" x 10 1/4" (483mm x 45mm x 260mm)