

Visual Performance Cinema Series Grilles



VP Cinema LCR1/SUR1 Grille

Fits the VP Cinema LCR1 and SUR1. The one-piece grille is made of perforated steel and plastic.



PART#	92690
UOM	PAIR

VP Cinema LCR2/SUR2 Grille

Fits the VP Cinema LCR2 and SUR2. The one-piece grille is made of perforated steel and plastic.



PART#	92691
UOM	PAIR

VP10SUB NC Grille

Visual Performance replacement grille for VP10SUB NC.



PART#	92894
UOM	EACH

VP12SUB NC Grille

Visual Performance replacement grille for VP10SUB and VP12SUB NC.



PART#	92895
UOM	EACH

Visual Performance Cinema Series Grilles

VP Cinema LCR/SUR In-Ceiling Grille

Fits the VP Cinema Series In-Ceiling speakers VP Cinema LCR1S, SUR1S and LCR.5S.



PART#	92882
UOM	PAIR

VP Cinema Medium Rectangle Metal Grille

Fits VP Cinema Select LCR and SUR speakers and all Original Series Medium rectangle speakers. The grille is made of perforated aluminum.



PART#	92100
UOM	PAIR

VP Cinema Cabinet LCR1 Grille

Black cloth replacement grille for Cinema Cabinet LCR1 speaker.




PART#	92883
UOM	EACH

Visual Performance Cinema Series Flex Brackets

VP Cinema LCR1/SUR1 Flex Bracket


Durable ABS flex bracket for new construction can be nailed, stapled, or screwed to studs before drywall is cut and installed. The speaker then installs using its Roto-Lock clamps. The Flex bracket's snap-on mesh metal wings will accommodate up to 24-inch (610mm) on-center installations and are configurable horizontally or vertically. Centering marks aid in proper alignment. It can be used only with VP Cinema LCR1 and SUR1 speakers.



PART#	92499
UOM	EACH

VP Cinema LCR2/SUR2 Flex Bracket

Durable ABS flex bracket for new construction can be nailed, stapled, or screwed to studs before drywall is cut and installed. The speaker then installs using its Roto-Lock clamps. The Flex bracket's snap-on mesh metal wings will accommodate up to 24-inch (610mm) on-center installations and are configurable horizontally or vertically. Centering marks aid in proper alignment. It can be used only with VP Cinema LCR2 and SUR2 speakers.



PART#	92500
UOM	EACH

VP Cinema In-Ceiling Flex Bracket

Durable ABS flex bracket for new construction can be nailed, stapled, or screwed to joists before drywall is cut and installed. The speaker then installs using its Roto-Lock clamps. The Flex bracket's snap-on mesh metal wings will accommodate up to 24-inch (610mm) on-center installations and are configurable horizontally or vertically. Centering marks aid in proper alignment. It can be used with the VP Cinema Series In-Ceiling speakers.



PART#	92800
UOM	EACH

Visual Performance Cinema Series In-Wall Acoustic Enclosures

Visual Performance Cinema Series In-Wall Subwoofer Enclosures

Feature a combination of 1/2" and 1" MDF materials for superior isolation of bass; extruded aluminum bracing for minimal obstruction of airflow inside the enclosure; mass damping of front and back walls of enclosure; long-strand fiberglass internal damping for standing wave dissipation; dual positive and negative terminals for maximum wire connectivity; floating enclosure design minimizes vibration transfer to adjoining rooms; fits in standard 2x4 stud bay; blank pre-construction plate for easy installation.

VP10SUB NC Enclosure

SPECIFICATIONS

Internal Volume:	.80 cubic feet (22.6 liters) of volume
Material:	MDF wood box with long strand fiberglass acoustic dampening material
Compatibility:	Fits the VP10SUB NC only
Enclosure Dimensions (WxHxD):	14 1/4" x 47 1/4" x 3 7/16" (362mm x 1200mm x 87mm)
Mounting Depth:	3 3/8" (85.7mm)
Mounting Bracket Width:	16 1/4" (409.5mm)
Hardware:	Integrated L-bracket mounting system included



PART# 92874
UOM EACH

VP12SUB NC Enclosure

SPECIFICATIONS

Internal Volume:	1.20 cubic feet (34.3 liters) of volume
Material:	MDF wood box with long strand fiberglass acoustic dampening material
Compatibility:	Fits the Sonance Cinema SUB12-500 only
Enclosure Dimensions (WxHxD):	14 1/4" x 70 7/8" x 3 7/16" (362mm x 1800mm x 87mm)
Mounting Depth:	3 3/8" (85.7mm)
Mounting Bracket Width:	16 1/4" (409.5mm)
Hardware:	Integrated L-bracket mounting system included



PART# 92875
UOM EACH