

Invisible Series

Invisible Series

- The benchmark for performance and installation flexibility for invisible speakers.
- Fully concealed within walls or ceilings for a totally invisible result.
- Speaker surface can be finished with up to 1/8" (3mm) of lightweight flexible material including finishing compound and paint, venetian plaster, wallpaper or wood veneer.
- Available in four models to accommodate any install or budget.
- Optional enclosure to reduce sound transfer to adjacent rooms.



IS2

Tweeter	4 sq. in (27 sq. cm) planar diaphragm, driven by a 1" (25mm) voice coil
Midrange	—
Woofers	50 sq. in (320 sq. cm) planar diaphragm, driven by a 1" (25mm) voice coil
Frequency Response	50Hz - 20kHz ±3dB
Impedance	8 ohms nominal; 6 ohms minimum

Power Handling 80 watts RMS
Sensitivity 88dB SPL (1 watt/1 meter)
Dispersion 170° hemispherical up to 10kHz
Finish Paper surface ready for up to 1/8" (3mm) flexible material* and paint *Pliable, elastic material such as joint compound, plaster or wallpaper.

Overload Protection Two independent self-resetting gel switches (low and high)

Environment Temperature 0° - 125° F (-17.7° - 51.7° C)

Speaker Depth 2" (51mm) 3 11/16" (94mm) With optional Enclosure

Shipping Weight 12 lbs (5.5kg) pair

UL Rating —

Cut-Out Dimensions (W x H) 16 1/8" x 12 1/8" (409.5mm x 307mm)

Transformer —