

VISUAL PERFORMANCE® SERIES

BPS8 BANDPASS SUBWOOFER WITH BANDPASS CONNECTOR VPBPC4R, VPBPC6R, + Square Adapter




Award Winning Visual Performance Series Aesthetic and Best-in-class Sonic Performance

The BPS8 Subwoofer is the latest evolution in the Sonance subwoofer line. Using state-of-the-art materials, the BPS8 delivers clean, powerful bass and the highest level of performance when

paired with the Visual Performance small or medium speakers. Featuring a low profile and micro trim bezel, they can be perfectly aligned with downlights and complement any architectural style.

Features and Benefits

- High-performance dual voice coil 8" high-excursion subwoofer for extended bass response with Sonance in-wall and in-ceiling speaker systems
- State-of-the-art driver materials combined with cutting-edge design technology ensures clean and accurate tonality and smooth powerful bass response
- Can be powered from dedicated output channel on amplifier for ultimate performance and control
- Or, can be connected in parallel with Sonance in-ceiling speakers for simplified installation
- Compact form factor provides flexibility for mounting in limited areas such as crawl-spaces and ceiling cavities



BPS8 Subwoofer




VPBPC4R



VP4SQ Adapter Kit



VPBPC6R



VP6SQ Adapter Kit

Aesthetics

- Award-winning low profile microtrim grille
- Paintable to match ceiling color
- VP4SQ and VP6SQ gives the speaker a square aesthetic (sold separately)
- Complement contemporary ceiling moldings & interior design

Installation


- One-piece grille with removable scrim cloth
- Simplified one-step painting process for a better finish
- Best-in-class fit and finish
- Magnetic retention system eliminates gaps between grille and ceiling, minimizing shadows
- Two-piece toggle feet

BPS8 Subwoofer can be installed in joists spaced 16" on center or greater

Dimensions


BPS8 Subwoofer

Height: 9 1/4" (235mm)
 Width: 12 5/16" (313mm)
 Depth: 24" (610mm)



BPS8 Port Tube

Diameter: 4 1/2" (114mm)
 Length: 22" (559mm)



VPBPC4R

Diameter: 6 5/16" (160mm)
 Depth: 4 5/8" (118mm)

With VP Round Grille



Diameter: 7" (178mm)
 *Included

With Square Adapter & Grille

Width x Height: 7" x 7"
 (178mm x 178mm)

*Sold separately


VPBPC4R




Round Grille



VP4SQ



Square Grille



VPBPC6R

Diameter: 9 3/16" (233mm)
 Depth: 4 3/4" (121mm)

With VP Round Grille



Diameter: 9 7/8" (251mm)
 *Included

With Square Adapter & Grille


Width x Height: 9 7/8" x 9 7/8"
 (251mm x 251mm)

*Sold separately


VPBPC6R




Round Grille



VP6SQ




Square Grille



BPS8 System Wiring Option 4.1

VP System Wiring Diagram - 2 Channel Amplifier



Home Run Wire to Each Speaker!


Impedance

SATELLITE	QUANTITY PER AMP CHANNEL	BPS8	SYSTEM MINIMUM IMPEDANCE
VP42R	2 Speakers	1	3.5 ohms
VP46R	2 Speakers	1	3.5 ohms
VP48R	2 Speakers	1	3 ohms
VP60R	2 Speakers	1	3.5 ohms
VP62R	2 Speakers	1	3.5 ohms
VP64R	2 Speakers	1	3.5 ohms
VP66R	2 Speakers	1	3.5 ohms
VP68R	2 Speakers	1	2.5 ohms

Use only Sonance Amplifiers

BPS8 System Wiring Option 4.1 with Subwoofer on Separate Channel

VP System Wiring Diagram - 8 Channel Amplifier



Home Run Wire to Each Speaker!


Impedance

SATELLITE	QUANTITY PER AMP CHANNEL	SATELLITE MINIMUM IMPEDANCE	BPS8	BPS8 MINIMUM IMPEDANCE PER VOICE COIL
VP42R	2 Speakers	3.5 ohms	1	6 ohms
VP46R	2 Speakers	3.5 ohms	1	6 ohms
VP48R	2 Speakers	3 ohms	1	6 ohms
VP60R	2 Speakers	3.5 ohms	1	6 ohms
VP62R	2 Speakers	3.5 ohms	1	6 ohms
VP64R	2 Speakers	3.5 ohms	1	6 ohms
VP66R	2 Speakers	3.5 ohms	1	6 ohms
VP68R	2 Speakers	2.5 ohms	1	6 ohms

Use only Sonance Amplifiers

BPS8 System Wiring Option 4.2

VP System Wiring Diagram - 2 Channel Amplifier



Home Run Wire to Each Speaker!

Impedance

SATELLITE	QUANTITY PER AMP CHANNEL	BPS8*	SYSTEM MINIMUM IMPEDANCE
VP42R	2 Speakers	2	7 ohms
VP46R	2 Speakers	2	7 ohms
VP48R	2 Speakers	2	6 ohms
VP60R	2 Speakers	2	7 ohms
VP62R	2 Speakers	2	7 ohms
VP64R	2 Speakers	2	7 ohms
VP66R	2 Speakers	2	7 ohms
VP68R	2 Speakers	2	5 ohms

*BPS8 Voice Coils Connected in Series



SPECIFICATIONS

BPS8

SKU	93044
UOM	Each
Woofer	8" (203mm) dual voice coil, carbon fiber / Rohacell laminated cone with a rubber surround
Frequency Response	30Hz – 90Hz ±3dB
Impedance	6 ohms nominal; 4 ohms minimum
Power Handling	150 watts maximum
Sensitivity	90dB SPL (2.83V/1 meter)
Dimensions Sub (H x W x D)	9 1/4" x 12 5/16" x 24" (235mm x 313mm x 610mm)
Dimensions Port Tube (Dia. x Length)	4 1/2" x 22" (114mm x 559mm)
Shipping Weight	45 lbs (20.41kg) each



SPECIFICATIONS

VPBPC4R

SKU	93096
UOM	Each
Grille	Shipped w/ Round 7" (178mm) perforated steel grille
Dimensions (Dia. x D)	6 5/16" x 4 5/8" (160mm x 118mm)
Shipping Weight	1.5 lbs (.68kg) each



SPECIFICATIONS

VPBPC6R

SKU	93097
UOM	Each
Grille	Shipped w/ Round 9 7/8" (251mm) perforated steel grilles
Dimensions (Dia. x D)	9 3/16" x 4 3/4" (233mm x 121mm)
Shipping Weight	3 lbs (1.36kg) each

BPS8 Associated Products

VP4SQ Square Adapter w/ Grille 93029
(Pair Per Box)



VP6SQ Square Adapter w/ Grille 93030
(Pair Per Box)



Small Round Flex Bracket 92471
(5 Pair Per Box)



VP4SQ Square Adapter w/ Grille 93032
(5 Pair Per Box)



VP6SQ Square Adapter w/ Grille 93033
(5 Pair Per Box)



Medium Round Flex Bracket 92337
(5 Pair Per Box)



Medium Round Coverplate 92335
(Pair Per Box)



* Best practice - Use a Sonance Flex Bracket when installing BPS8 and VPBPC

Sonamp DSP 8-130 MKII Amplifier 93094
(Each)



Sonamp DSP 2-150 Amplifier 93093
(Each)



Sonamp 2-100 Amplifier 93091
(Each)



LIMITED WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand Subwoofer product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for fifteen (15) years. The Band Pass Connectors have a limited lifetime warranty, the grille is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent.



©2015 Sonance. All rights reserved.

Sonance, Visual Performance and Roto-Lock, are registered trademarks of Dana Innovations.

Due to continuous product improvement, all features and specifications are subject to change without notice.

For the latest Sonance product specification information visit our website: www.sonance.com

SONANCE • 991 Calle Amanecer • San Clemente, CA 92673 USA

(949) 492-7777 • FAX: (949) 361-5151 • Technical Support: (949) 492-7777

www.sonance.com