

SONANCE 



# BPS6 THINLINE SUBWOOFER



**BPS6 TL**

Sonance is proud to announce the BPS6 TL, the first ever Discreet Opening System Thinline Subwoofer. Created for Architectural Series and Visual Performance Series, this in-wall or in-ceiling subwoofer is designed for tight spaces with restricted mounting depths.



**BPS6 TL**  
**SKU 93324**  
**MSRP \$1,100 (each)**

---

<b>Woofers:</b>	13" (330mm) x 3" (76mm) Laminated Carbon Fiber Cone with a Rubber Surround, Dual Voice Coil
<b>Frequency Response:</b>	38Hz - 125Hz $\pm$ 3dB
<b>Impedance:</b>	6 Ohms nominal
<b>Power Handling:</b>	50 Watts minimum; 150 Watts maximum
<b>Sensitivity:</b>	87dB @ 2.83V / 1 meter
<b>Dimensions: (H x W x D)</b>	39 3/8" x 11" x 3 3/8" (1000mm x 279mm x 86mm)
<b>Port Tube Dimensions: (Dia. x L)</b>	3" x 15" (76mm x 381mm)

---

	<b>Architectural Series Bandpass Connector SKU 93334</b>	<b>Visual Performance Series Bandpass Connector SKU 93335</b>
<b>Bandpass Connector:</b>	ASBPC3RS TL	VPBPC3R TL
<b>Dimensions: (Dia. X D)</b>	3 7/8" x 2 1/4" (99mm x 57mm)	4 5/16" x 3 1/2" (109mm x 89mm)
<b>Grille Dimensions: (Dia.)</b>	ASBPC3RS TL shipped with Round 4" (102mm) and Square 4" (102mm) perforated steel grilles	VPBPC3R TL shipped with Round 4 29/32" (124mm) perforated steel grilles