

HD-TVI Wall Mount Digital Video Recorder with Built-In Power Supply



4 Channel HD-TVI Wall Mount DVR with Built-in Power Supply

8 Channel HD-TVI Wall Mount DVR with Built-in Power Supply











STORAGE 1TB - 8TB







Key Features

EZ Wizards - For ease of use and setup

Setup: for quick setup of general settings

Network: network setup and port forwarding

Record: quickly setup recording resolutions and recording type

Search: quickly search for events from thumbnails

Copy: quickly copy what you are playing onto a USB flash drive

- A patented DVR solution that easily mounts in equipment closets or electrical rooms for covert installations
- Supports up to 4MP @ 15fps over coax
- Supports up to 3MP @ 18fps over coax
- Supports up to 2MP @ 30fps over coax
- Backward compatible with all analog cameras
- UTC function allows for zoom/focus and OSD control over coax
- H.264 video compression
- Tamper resistant, 20 gauge powder coated steel
- Surface or flush mountable
- Free U.S. Based DDNS Server Access
- 5 year limited warranty²

Additional Features

- Signal distance up to 1600 feet¹
- Video Out: 1 HDMI®, 1 VGA, 1 CVBS
- Digital Deterrent® supports up to 8 audio files for triggering during sensor or motion detection
- 2-way audio communication
- Built-in S.M.A.R.T. Technology(Self-Monitoring, Analysis and Reporting Technology for HDD)
- 4 channel audio recording
- Password to secure installation authorization
- Smart (Museum) Search Quickly search for a specific video event without the need for motion setup.
- Easy firmware upgrade by USB port
- Instant and convenient backup via USB flash drive
- Supports multiple PC based browsers such as Internet Explorer and Firefox
- Simultaneous playback/record while continuing to network transfer or backup
- User Access: up to 12 concurrent users for live viewing, 1 user for playback
- Remote monitoring / recording / playback / configuration / software upgrades and PTZ control via internet
- Network accessible via SpecoTech Multi-Client Software, SecureGuard®, Web-Viewer and Speco Player Mobile app
- PC and MAC® compatible
- IR remote control and mouse included

Optional Accessory

POE16SW18 16 PoE Port 10/100 802.3af/ at Switches

To preserve signal quality and distance, Speco Technologies recommends using coax with 100% copper center conductor and at least 95% braided copper shield. 2Hard drives excluded. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc.The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/8/18












	Models		D4WVXP	D8WVXP	
	Input	Number of Channels	4	8	
Video	трог	Camera Types	960H, HD-TVI 1/2	2/3/4MP	
Video		Main Monitor	VGA and HDMI (Max	. 1920x1080)	
	Output	Sub Monitor	CVBS or SPOT (S	electable)	
	Input & Output		4 line input & 1 line output		
Audio	Audio Codec		G.711		
	2-Way Audio		Local Port Network Client		
	Sensor Input		4	4 or 8 (with Sensor Box)	
Alarm	Alarm	Output	1		
Serial	RS-	485	1		
	Frame Rate with 4MP Cameras		15fps/channel		
Live	Frame Rate with 3MP Cameras		18fps/channel		
	Frame Rate with 2MP Cameras		30fps/channel		
	Compression 2688×1520 (4MP)		H.264		
			<u> </u>	10fps/channel	
	Resolution & Frame Rate	2304×1296 (3MP)	13fps/chan		
Recording	1920×1080 (2MP)		15fps/channel		
	Recording Quality Grade		5 Levels		
	Recording Mode			Smart / Continuous / Motion / Sensor / Schedule / Manual	
	Pre-Recording			Max. 20 minutes	
	Post Recording			Max. 60 seconds	
	Search Mode		EZ Search, Smart (Museum) Search, Timeline, Event, Archive, Log		
Playback	Multi-Decoding		1, 4		
	Playback Speed		x0.25, x0.5, x2, x4, x8,	x0.25, x0.5, x2, x4, x8, x16, x32, x64	
	Media		USB Drive, External HDD, Network		
Backup	Format		BMP, AVI, Proprietary Format and EXE		
	Huge Backup		Yes (Max. 24 hours)		
Storage		Capacity of 1 HDD	8TB		
	HDD	Internal HDDs	1		
		e-SATA	-		
		Front	1		
	035	Rear	1		
User I/F	Input A	Nethod	IR Remote Control, Mouse, Keyboard Controller		
	Interface		10/100/1000 Base-TX		
Network	Dynamic DNS		Yes (Free DDNS)		
	Dual Streaming		Yes		
	3G M	lobile	iPad® / iPhone® /	^ Android™	
	Web Viewer		Windows (Internet Ex	olorer, Firefox)	
Network Access	PC C	lient	SpecoTech Multi-Client Viewer a	SpecoTech Multi-Client Viewer and SecureGuard® VMS	
	MAC Client		Speco Client for MAC and S	Speco Client for MAC and SecureGuard® VMS	
	Remote Setup and Upgrade		Yes		
				1 01	
	Digital De	eterrent®	Default + up to 8 custo	om audio tiles	
			Default + up to 8 custo Yes	om audio files	
	Digital De	Zoom		om audio tiles	
	Digital Do Digital Do Digital	Zoom	Yes	m audio tiles	
	Digital Di Digital DST (Daylig EZ Re	Zoom ht Savings)	Yes Yes	om audio tiles	
Features	Digital Do Digital DIST (Daylig EZ Ro	Zoom ht Savings ccord A.R.T	Yes Yes Yes Yes		
Features	Digital DIGITA	Zoom Iht Savings) ecord A.R.T Il Beep	Yes Yes Yes Yes Yes Septimized to the septimized	DD error	
Features	Digital DIGITA	Zoom pht Savings) ecord A.R.T al Beep unguage	Yes Yes Yes Yes Yes By video loss, HI English / Spanish	DD error / French	
Features	Digital DIGITA	Zoom ght Savings) scord A.R.T al Beep unguage	Yes Yes Yes Yes By video loss, Hl English / Spanish USB upgra	DD error / French	
Features	Digital DIGITA	Zoom Int Savings) scord A.R.T al Beep Inguage Ingrade Intification	Yes Yes Yes Yes Sey video loss, HI English / Spanish USB upgra Yes	DD error / French	
	Digital Du Digital Du Digital DST (Daylig EZ Re S.M Interne Multi-Le SW Up Email No	Zoom pht Savings) scord A.R.T al Beep inguage sigrade stification Time Protocol)	Yes Yes Yes Yes Sey video loss, HI English / Spanish USB upgra Yes Yes	DD error / French de	
Power	Digital DIGITA	Zoom John Savings) scord A.R.T al Beep singuage ograde stification Time Protocol) ply Voltage	Yes Yes Yes Yes Seyvideo loss, HI English / Spanish USB upgro Yes Yes Yes Yes	DD error / French de	
Power Allowa	Digital Do Digital Digital DST (Daylig EZ Re S.M Internot Multi-La SW Up Email Na NTP (Network Power Sup)	Zoom pht Savings) acord A.R.T al Beep anguage agrade stification Time Protocol) ply Voltage umidity	Yes Yes Yes Yes Yes By video loss, HI English / Spanish USB upgra Yes Yes 12VDC 3 41°F-104°F/20	DD error / French de A % - 80% RH	
Power Allowa	Digital DIGITA	Zoom pht Savings) acord A.R.T al Beep inguage agrade stification Time Protocol) ply Voltage umidity	Yes Yes Yes Yes Seyvideo loss, HI English / Spanish USB upgro Yes Yes Yes Yes	DD error / French de A % - 80% RH	















Channel	HDD	Base Model
	1TB	D4WVXP1TB
	2TB	D4WVXP2TB
4	ЗТВ	D4WVXP3TB
4	4TB	D4WVXP4TB
	6ТВ	D4WVXP6TB
	8TB	D4WVXP8TB
	1TB	D8WVXP1TB
	2TB	D8WVXP2TB
	ЗТВ	D8WVXP3TB
8	4TB	D8WVXP4TB
	6ТВ	D8WVXP6TB
	8TB	D8WVXP8TB



