



# 4MP Flexible Intensifier® HD-TVI Motorized Zoom Focus Camera with Junction Box, Dual Voltage

## H4FD2M

2.7 - 12mm motorized zoom focus lens, dark gray housing

### Features

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30FPS
- True WDR operation
- Adaptive IR LED's
- Presets: Outdoor, Low Light, Hallway, Lobby, Elevator, Indoor
- Built-in heater and anti-fog glass reduces condensation
- 3-axis for wall and ceiling mounting
- Chameleon Cover™: snaps on and can be painted to match any décor!\*
- Full OSD and Zoom / Focus control through on-board and UTC
- Signal distance up to 1600 feet\*
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- 12VDC & 24VAC dual voltage operation
- 5 year warranty



### Camera Specifications

Image Sensor	1/2.8" SONY STARVIS 6MP Sensor
Minimum Illumination	0.00 lux (IR LED 'on')
Effective Pixels	2616 (H) x 1964 (V)
Total Pixels	2704 (H) x 2104 (V)
Scanning System	Progressive
S/N Ratio	More than 50dB
Video Output	1.0Vp-p / 75 Ohms
Electronic Shutter	Auto / Manual (1/30 - 1/30,000 sec.)
WDR	On (Low / Middle / High) / Off
Day / Night	Auto / Intensifier
Test Monitor Output	TVI out
Power	12VDC / 24VAC
Power Consumption	700mA max. (DC), 500mA max. (AC)
Operating Temperature	-40° F - 140° F
Unit Dimensions	3.97" (H) x 5.23" (Dia.)
Unit Weight	1.4 lbs (camera), 0.7 lbs (junction box)
Certifications	FCC, RoHS

\*with compatible Speco recorder

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

### Optional Accessories



**PSW5**  
12VDC  
Power Supply



**PSW4**  
24VAC 50VA  
Power Supply



**INTCM1**  
Corner Mount



**INTWM1**  
Wall Mount



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. x/x/24

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • www.specotech.com

