

4 to 2 HDMI® Matrix

HD4MAT

Features

Matrix units are used when one has multiple HDMI sources such as DVRs or DVD players and wants to split these sources to two different monitors or televisions.

- Takes 4 HDMI sources and divides them to 2 HDMI devices
- Supports 3D HDMI signals
- Supports resolutions up to and including 1080p
- Supports DTS/Dolby/DTS-HD/Dolby True HD/LPCM7.1/AC3
- Supports HDCP 1.2
- Supports simultaneous digital audio output: Stereo, Toslink and Coax
- Includes IR remote control




front of unit



rear of unit

Specifications

Operating Temperature..... 14° F – 176° F
 Operating Humidity..... 5% – 90% RH (no condensation)
 Input Video Signal 1.2Vp-p
 Data Transfer Speed Rate..... 10.2 Gbps (max)
 Power Supply 5VDC (power supply included)



- A** HDMI inputs from sources
- B** HDMI outputs to monitors

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.
 Spec Rev. 2/18/14

