

1000TVL Intensifier® Dome Camera

HTINT59K1

2.8-12mm varifocal lens, dark gray housing







Features

- 1/3" 1.3MP Sensor
- 1000 TV lines highest resolution in analog
- Superior low-light performance
- True WDR operation
- Amplify existing light with no distance limitation
- Built-in heater and anti-fog glass reduces condensation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator
- 3-axis for lens mount

- Full OSD operation through on-board control
- Chameleon CoverTM: snaps on and can be painted to match any décor!*
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- 12VDC & 24VAC dual voltage operation
- 5 year warranty
- NDAA Compliant*





Shown with included paintable, snap-on Chameleon Cover



Camera Specifications	
Image Sensor	1/3" CMOS, 1.3MP
Minimum Illumination	0.0001 lux (sense-up x32)
Effective Pixels	1305 (H) x 1049 (V)
Total Pixels	1312 (H) x 1069 (V)
Scanning System	Progressive
S/N Ratio	More than 50dB
Output Resolution	1000TVL
Video Output	1.0Vp-p / 75 Ohms
Electronic Shutter	Auto/Manual (1/60 - 1/60,000 sec.)
WDR	On (Low/Middle/High)/Off
Day/Night	Auto/Color/BW/External
White Balance	Auto/AWB/AWC-Set/Manual
Brightness	0 - 20 (adjustable)
AGC	0 - 10 (adjustable)
Sense-up	2x - 32x (adjustable)
Backlight	BLC/HLC

On/Off (4 zones)

On/Off (16 zones)

0 - 10 (adjustable)

Off/Low/Middle/High

On/Off

On/Off

Operating & Unit Specifications

Power	12VDC/24VAC dual voltage (power supply included)
Power Consumption	12VDC, 500mA max. 24VAC, 195mA max.
Operating Temperature	-4°F - 122°F
Unit Dimensions	3.95" (H) x 5.24" (Dia)
Unit Weight	3 lbs.
Certifications	FCC, RoHS



*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessory



Motion Detection

Privacy Masking

Mirror

Flip Sharpness

DNR





INTWM1 Wall Mount (use with Junction Box)



INTCM1 Corner Mount (use with INTWM1)

