



# 4K 32 Channel Facial Recognition, NDAA Compliant Wall Mount NVR with Smart Analytics and Dual LAN Ports

## N32WNRN

32 Channel NVR with 2 Ethernet Ports

### Key Features

- EZ Wizards:** For ease of use and setup
- Camera:** Quickly discover and install all Speco Blue IP cameras
- Setup:** Quick setup of general settings
- Network:** Setup and port forwarding
- Record:** Quickly setup recording resolutions and recording type
- EZ Search 2.0:** Quickly find an event using time-sliced thumbnail images of your recordings with quick preview
- Copy:** Quickly copy what you are playing onto a USB flash drive
- EZ Mobile:** Easy mobile setup for viewing on desktop or mobile apps

- Two LAN Ports to help isolate camera traffic from the main network
- Real time recording up to 12MP resolution (4K) at 20fps and 8MP resolution at 30fps
- H.265 compression - Store up to 2x more than H.264!
- 2 HDMI out and one VGA monitor output
- 4 SATA ports for up to 20TB of storage per SATA for a maximum of 80TB
- Manage the N32NRN through our Speco Dashboard
- Supports RAID 0,1,5,6,10
- Facial Recognition (up to 6 Channels)\*\*
- Object and Line Crossing Detection and Alerts\*
- Smart Search - Specify a region on the camera view and search on changes in that area\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, or your mobile device
- Easy video exporting via USB
- Remote control included
- 5-year limited warranty

\*with Speco Smart Analytic Cameras

\*\*with Speco Facial Detection Cameras

### Additional Features

- Find and install IP cameras on the local network without needing to locate the cameras manually
- Supports different recording types: Continuous, Motion, Analytics, and Sensor
- Create bookmark pins on playback for easy reference
- Instant playback for individual channels directly from the live view screen
- Customizable channel view placement
- Remote monitoring, recording, playback, configuration, upgrades, and PTZ control via the Internet
- Simultaneous HDMI & VGA video output
- Supports 2-way audio communication (speaker required)



### Compatible Apps



- One app to view your Speco Devices on go\*



- Access your NR and HR Series Recorder to view and playback videos from your mobile device.

**INCREASE YOUR MONTHLY REVENUE**

Remotely Manage from Anywhere with SecureGuard® Dashboard

### Included Accessories



(1) Remote Control

### Optional Accessories



**P32S36GM**  
36-Port Managed Gigabit Switch with 32-ports PoE and 4xSFP Uplink

### Storage: 4TB - 80TB

|             |             |             |
|-------------|-------------|-------------|
| N32WNRN4TB  | N32WNRN20TB | N32WNRN60TB |
| N32WNRN6TB  | N32WNRN24TB | N32WNRN64TB |
| N32WNRN8TB  | N32WNRN32TB | N32WNRN80TB |
| N32WNRN12TB | N32WNRN40TB |             |
| N32WNRN16TB | N32WNRN48TB |             |



\*Does not have built in DHCP server



Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 4/3/24

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • www.specotech.com





# 4K 32 Channel Facial Recognition, NDAA Compliant Wall Mount NVR with Smart Analytics and Dual LAN Ports

| Model             |                            | WNRN                     |  |
|-------------------|----------------------------|--------------------------|--|
| Video             | Input                      | Max. IP Channels         | 32   |
|                   |                            | IP Camera                | H.264/H.265 Auto Detection (Max. 8MP)  |
|                   | Output                     | Main Monitor             | HDMI (Max. 4K) and VGA (Max. Full HD)  |
| VGA               |                            | VGA                      |  |
| Audio             | Network Input              |                          | 32 Ch. audio input   |
|                   | 2-way Audio                |                          | RCaX1  |
|                   | Local Output               |                          | RCaX1  |
| Recording         | Encoding Resolutions       |                          | 12MP/8MP/5MP/4MP/3MP/1080P/720P  |
|                   | Codec                      |                          | H.264/H.265 (Auto Detection)   |
|                   | Max Frame Rate per Channel |                          | 12MP 20fps/8MP or lower @30fps   |
|                   | Recording Mode             |                          | Analytics/Continuous/Motion/Sensor/Schedule/Manual   |
|                   | Pre-Recording              |                          | Max. 5 seconds   |
|                   | Post Recording             |                          | Max. 10 minutes  |
| Search & Playback | Search                     |                          | EZ Search, Motion, Specific Date/Time, Event, Museum, Bookmarks, Snapshots, Log  |
|                   | Simultaneous Playback      |                          | Max. 16 Ch.  |
|                   | Smart Search               |                          | Highlighted color to display camera records in a certain period of time, different colors refer to different record events |
|                   | Playback Functions         |                          | Play, Pause, FF, Rew, Digital Zoom, etc.   |
| Backup            | Media                      |                          | USB drive, Network   |
|                   | Format                     |                          | JPG, AVI, Proprietary Format (Includes Player)   |
| Storage           | HDD                        | Max Capacity of each HDD | 20TB   |
|                   |                            | Internal SATA ports      | 4  |
|                   | USB                        | Front                    | 1 USB 2.0  |
|                   |                            | Rear                     | 1 USB 2.0, 1 USB 3.0   |
| Alarm             | Mode                       |                          | Manual, Sensor, Motion, Exception, AI  |
|                   | Input/Output               |                          | 16ch local inputs, 9ch output  |
|                   | Linkage                    |                          | Record/Snapshot/Preset/Email/Pop-up Window   |
| User I/F          | Input Method               |                          | IR Remote, Mouse   |
| Network           | Network Bandwidth          |                          | 320Mbps  |
|                   | P2P/Dynamic DNS            |                          | Free US-Based Speco P2P and DDNS Service   |
|                   | Network Protocols          |                          | TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP  |
| Network Access    | Mobile                     |                          | iOS/Android via Speco Blue App, SecureGuard® Client  |
|                   | VMS/CMS                    |                          | Speco Blue VMS, SecureGuard®   |
|                   | Max. User Access           |                          | Max 10 users online (web client)   |
| Features          | Digital Zoom               |                          | Live and Playback, Free Size   |
|                   | S.M.A.R.T                  |                          | Temperature, Power On Time, Bad Sectors and Health   |
| Smart Analytics   | People / Vehicle Detection |                          | Line Crossing, Intrusion, People Counting  |
|                   | Facial Recognition         |                          | Store up to 10,000 face images<br>Up to 6CH for event<br>Face Search up to 32CH  |
|                   | LPR                        |                          | LPR on all 32CH, store up to 50,000 License Plate images   |
|                   | Others                     |                          | Object abandoned/missing, trip wire  |
| Power             | Power Consumption          |                          | ≤ 30W (without HDD)  |
| Environment       | Operating Temperature      |                          | 14°F to 122°F (-10°C to 50°C)  |
|                   | Operating Humidity         |                          | 10% - 90% humidity   |
| Dimensions        | Unit                       |                          | 489mm x 413mm x 89mm (19.25" x 16.25" x 3.5")  |