



4K H.265 NVR with Smart Analytics

Without Monitor

N4WNRM

4-Channel with 4 Built-In PoE Ports

N8WNRM

8-Channel with 8 Built-In PoE Ports

N16WNRM

16-Channel with 16 Built-In PoE Ports

With Monitor

N4WNRMM

4-Channel with 4 Built-In PoE Ports with Monitor

N8WNRMM

8-Channel with 8 Built-In PoE Ports with Monitor

N16WNRMM

16-Channel with 16 Built-In PoE Ports with Monitor



N8WNRM Shown




INCREASE YOUR MONTHLY REVENUE
Remotely Manage from Anywhere with SecureGuard® Dashboard

Product Summary

Speco's NDAA compliant WNRM recorders, will take your footage quality to the next level supporting up to 8MP cameras @ 30fps.

Features

- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression - Store up to 2x more than H.264!
- 4K HDMI output and one VGA monitor output
- N4WNRM: 1 SATA port for up to 16TB of storage max
N8WNRM: 1 SATA port for up to 16TB of storage max
N16WNRM: 2 SATA port for up to 32TB of storage max
- Facial detection*
- Object and line crossing detection and alerts**
- Smart Search - Specify a region on the camera view and search on changes in that area**
- Free US-based DDNS and P2P services
- Remote viewing via web browser or your mobile device
- Easy video exporting via USB
- Remote control included
- 5-year limited warranty

*With Speco Facial Detection Cameras

**With Speco Smart Analytic Cameras

Compatible Apps



• One app to view your Speco Devices on the go*



• Access your NR and HR Series Recorder to view and playback videos from your camera.

Storage: 2TB - 32TB

Without Monitor

N4WNRM2TB	N4WNRM8TB
N4WNRM4TB	N4WNRM12TB
N4WNRM6TB	N4WNRM16TB

With Monitor

N4WNRMM2TB	N4WNRMM8TB
N4WNRMM4TB	N4WNRMM12TB
N4WNRMM6TB	N4WNRMM16TB

N8WNRM2TB	N8WNRM8TB
N8WNRM4TB	N8WNRM12TB
N8WNRM6TB	N8WNRM16TB

N8WNRMM2TB	N8WNRMM8TB
N8WNRMM4TB	N8WNRMM12TB
N8WNRMM6TB	N8WNRMM16TB

N16WNRM2TB	N16WNRM12TB
N16WNRM4TB	N16WNRM16TB
N16WNRM6TB	N16WNRM24TB
N16WNRM8TB	N16WNRM32TB

N16WNRMM2TB	N16WNRMM12TB
N16WNRMM4TB	N16WNRMM16TB
N16WNRMM6TB	N16WNRMM24TB
N16WNRMM8TB	N16WNRMM32TB

Optional Accessories



P4S50
5-port IP65 Rated 4 port PoE Switch



P8S10G
10-Port Gigabit Network Switch (8 ports PoE, 2 ports uplink)



P4S5V
5-Port Gigabit Network Switch (4 ports PoE, 1 port uplink)



P24S26G2
26-Port Gigabit Switch with 24-PoE Ports and 2 SFP Uplink



P32S36GM
36 Port Managed Gigabit Switch (32 ports PoE, 4xSFP Uplink)



Model		WNRM			
		4	8	16	
Video	Input	Max. IP Channels	4	8	16
		IP Camera	H.264/H.265 Auto Detection (Max 8MP)		
	Output	Main Monitor	HDMI (Max. 4K) and VGA (Max. Full HD)		
Audio	Network Input		4 Ch. IPC audio input	8 Ch. IPC audio input	16 Ch. IPC audio input
	Local Input		RCAx1		
	Local Output		RCAx1		
Recording	Encoding Resolutions		8MP/6MP/4MP/3MP/1080P/720P/960H/DI/CIF		
	Codec		H.264/H.265 (Auto Detection)		
	Max Frame Rate per Channel		Any Resolution @30fps		
	Recording Mode		Analytics/Continuous/Motion/Sensor/Schedule/Manual		
	Pre-Recording		Max. 5 seconds		
	Post Recording		Max. 10 minutes		
Search & Playback	Search		EZ Search, Motion, Specific Date/Time, Event, Museum, Bookmarks, Snapshots, Log		
	Simultaneous Playback		Max 4 Ch.	Max 8 Ch.	Max 16 Ch.
	Smart Search		Highlighted color to display camera records in a certain period of time, different colors refer to different record events		
	Playback Resolutions		1 x 8MP @ 30 FPS, 6 x 1080P @ 30 FPS		
	Playback Functions		Play, Pause, FF, Rew, Digital zoom, etc.		
Backup	Media		USB drive, Network		
	Format		MP4, JPG, AVI, Proprietary Format (Includes Player)		
Storage	HDD	Max Capacity of each HDD	16TB		
		Internal SATA ports	1	1	2
	USB	Front Rear	1 (USB 2.0) 1 (USB 2.0)		
Alarm	Mode Input/ Output Linkage	Manual, Sensor, Motion, Exception, Intelligence IPC Alarm in / IPC Alarm out Record/Snapshot/Preset/Email/Pop-up Window			
User I/F	Input Method		IR Remote, Mouse		
Network	Network Bandwidth		80Mbps	80Mbps	144Mbps
	P2P/Dynamic DNS		Free US-Based Speco P2P and DDNS Service		
	Network Protocols		TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP		
Network Access	Mobile		iOS/Android via Speco Blue App, SecureGuard® Client		
	Web Viewer		Chrome, Edge, Firefox		
	VMS/CMS		Speco Blue VMS, SecureGuard®		
	Max. User Access		Max 64 users access		
Features	Digital Zoom		Live and Playback, Free Size		
	S.M.A.R.T.		Temperature, Power On Time, Bad Sectors, and Health		
Smart Analytics	People/Vehicle Detection		4	8	16
	Facial Detection		4	8	16
	License Plate Recognition		4	8	16
Power	Power Consumption		≤ 10W (without HDD)		
	PoE Ports		4	8	16
	Power per PoE Port		15.5W (802.3af)		
	Total PoE Power Budget		48W	72W	150W
Environment	Operating Temperature		14°F to 122°F (-10°C to 50°C)		
	Operating Humidity		10% - 90% humidity		
Dimensions	Unit		387mm x 298mm x 89mm (15.25" x 11.75" x 3.5")		489mm x 413mm x 89mm (19.25" x 16.25" x 3.5")



*Products are in compliance with NDA Section 889 Part B Guidelines



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 5/30/24

800.645.5516 • Fax: 631.957.9142 or 631.957.3880 • www.specotech.com

