


## 2MP Intensifier IP® Corner Mount IP Camera

**O2i605CM** 2.9mm fixed lens, stainless steel housing



### Features

- See color in low light without IR LEDs
- Supports up to 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- No problems caused by objects that reflect or absorb IR light sources
- With presets for different scenarios
- Attached cable (8 ft.) connects camera unit to main unit for flexible placement
- Perfect for use in elevators
- 2-way audio communication
- Sensor input and relay output
- Micro SD card slot (card not included)
- Conformant with ONVIF Profile S
- 5 year warranty\*

### Camera Specifications

Image Sensor ..... Progressive scan 1/2.8" CMOS, 2MP  
 Maximum Resolution ..... 1920 x 1080  
 Minimum Illumination ..... F1.4, Color: 0.2 lux (Max Intensify)  
 White Balance ..... ATW/AWB  
 Compensation ..... WDR  
 Intensify ..... Selectable (max 8x) / Off  
 Electronic Shutter Speed ..... 1/30 - 1/10000 sec  
 DNR ..... 2D/3D

### Video Specifications

Main Resolution ..... 1920x1080 / 1280x720 @ 30fps  
 Compression ..... H.264 (HP/MP/BP), MJPEG  
 Bitrate Control ..... VBR, CBR  
 Multiple Streaming ..... 3 streams

### Audio Specifications

Mono Input ..... G.711  
 Mono Output ..... G.711

### External Terminal Specifications

Ethernet ..... 10/100 Mbps  
 Alarm ..... 1 sensor input, 1 relay output (terminal block)  
 Audio ..... 1 mic in, 1 line out (terminal block)  
 Power ..... Terminal block

### Network Specifications

Protocols ..... IPv4, TCP, UDP, RTP, RTSP, HTTP, HTTPS, SMTP, FTP, DHCP, UPnP, DNS  
 DDNS support ..... Speco DDNS (free of charge)

### Network Specifications (continued)

Security ..... User ID & Password protection, IP address filtering, digest authentication  
 User Access ..... Max. 8 simultaneous users. Actual number of users may vary depending on bandwidth

### System Specifications

PoE ..... Standard (IEEE 802.3af)  
 Analytics ..... Motion detection, tampering, sensor input  
 Alarm Triggers ..... Analytics  
 Alarm Events ..... FTP upload, email upload, micro SD card recording, relay output

Image Settings ..... Privacy mask

### Client Specifications

Web Browser Support ..... Windows (Internet Explorer 8 and up)  
 PC Application ..... SecureGuard® VMS  
 Mobile ..... SecureGuard® Mobile (iPhone® and Android™)

### Operating & Unit Specifications

Power Supply ..... PoE, 12VDC (power supply not included)  
 Power Consumption ..... 4W  
 Operating Temperature ..... 14° F – 122° F  
 Operating Humidity ..... 0% - 90% RH  
 Main Unit Dimensions ..... 2.59" (W) x 1.24" (H) x 4.21" (D)  
 Main Unit Weight ..... 5 oz.  
 Camera Unit Dimensions ..... 9" (W) x 7" (H) x 4" (D)  
 Camera Unit Weight ..... 1.4 lbs.  
 Certifications ..... FCC, RoHS

### Optional Accessories



**POEINJ**  
12.95W  
PoE Injector



**PSW5**  
12VDC  
Power Supply

\*Effective on all new purchases as of 2/1/17. Visit [www.specotech.com](http://www.specotech.com) for latest ONVIF support. ONVIF is a trademark of Onvif, Inc. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/6/17