O2iB68M

2.7-12mm motorized lens, dark gray housing

Features

- Intensifier® allows low light performance without IR LEDs
- Motorized lens with auto focus
- Supports up to 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- Scene Presets for different lighting conditions
- Supports H.264 and MJPEG codecs
- 2-way audio communication

• Micro SD card slot (card not included)

- Sensor input and relay output
- Built-in heater to prevent condensationIP66 compliant, weather resistant
- IPOO compliant, weath
 Junction box included
- Conformant with ONVIF Profile S
- 5 year warranty

Camera Specifications		
Image Sensor	Progressive scan 1/3" CMOS, 2MP pixels	
Maximum Resolution	1920×1080	
Field of View	113.54° (W)~33.4° (T) Horizontal, 59.3° (W)~18.78° (T) Vertical	
Minimum Illumination	F1.4, Color: 0.05 lux (Max Intensify)	
White Balance	ATW/AWB	
Compensation	Digital WDR	
Day/Night	IR cut filter	
Intensify	Selectable (max 32x) / Off	
Electronic Shutter Speed	1/30~1/10000 sec	
DNR	2D+3D	
Video Specifications		
Main Resolution	1920x1080 / 1280x720 @ 30fps	

OPERATES IN -40°F

Included Junction Box



Audio Specifications		
Mono Input	G.711	
Mono Output	G.711	
External Terminal Specifications		
Ethernet	10/100 Mbps	
Alarm	1 sensor input, 1 relay output	
Audio	1 mic in, 1 line out	
Power	DC jack	
System Specifications		
PoE	Standard (IEEE 802.3af)	
Analytics	Motion detection, Tampering alarm	
Alarm Triggers	Analytics & sensor input	
Alarm Events	FTP upload, email upload, relay out	
Image Settings	Privacy mask	
Operating & Unit Specifications		
Power	PoE, 12VDC (power supply not included)	
Power Consumption	7.5W	
Operating Temperature	-40°F - 140°F	
Operating Humidity	0% - 90% relative humidity	
Unit Dimensions	2.83" (W) × 2.83" (H) × 10.3" (D)	

Bitrate Control

Compression

Multiple Streaming

Network Specifications

Protocols	HTTP, HTTPS, FTP, SMTP, UPnP, DNS, DDNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, SNMP
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP address filtering, digest authentication
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth
Client Specifications	

H.264 (HP/MP/BP), MJPEG

VBR, CBR

3 streams

Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS
Mobile	SecureGuard [®] Client (iPhone [®] and Android [™])

Optional Accessories

Unit Weight Certifications



2.6 lbs

FCC, RoHS

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 4/10/20



