

4MP Flexible Intensifier® IP Turret Camera with Advanced Analytics, NDAA

04FT1

2.8mm fixed lens, dark gray housing















- Flexible Intensifier® Technology to fit any lighting application
- Captures up to 4MP @ 30fps real time
- Captures color in extreme low light conditions and monochrome in absolute darkness.
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Micro SD card slot (card not included)

- ONVIF Profile T Compliant
- IP67 Weather Resistance
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection*
- Face/Person/Vehicle detection*
- Junction box included
- 5 year warranty







Camera	Speci	fications

Progressive scan 1/1.8"CMOS
2560 × 1440
Horizontal: 111.3°; Vertical: 78.9°; Diagonal: 118.4°
0.0016 lux@F1.6, AGC ON; 0 lux with IR
Auto, Indoor, Outdoor, Manual
True WDR (120dB), BLC, HLC
Smart IR
1s~1/100000s
3D DNR
Pan: 0°~360°; Tilt: 0°~75°; Rotation: 0°~360°

Video Specifications

Main Resolution	2560×1440, 2304×1296, 1920x1080, 1280x720, D1, CIF, 480×240 @30fps		
Substream	1280x720, D1, CIF, 480×240 @30fps		
Third Stream	D1, CIF, 480×240 @30fps		
Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG		
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)		
Multiple Streaming	3 streams		
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Exposure, Gain, Corridor Pattern, Image flip/mirror		

Audio Specifications

Audio Compression	Compression G.711A / G.711U	
Audio input	Built-in mic and 3.5mm input	
Audio output	No	
Client Specifications		
Web Browser Support	Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari	
Web Browser Support PC Application	Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari SecureGuard® VMS and SecureGuard CMS	

SecureGuard® Client, Speco Blue

Interfaces

Ethernet	RJ45 Jack, 10/100 Mbps, PoE
Power	12VDC input jack
Audio	Built-in mic and 3.5mm input
Card slot	MicroSD, up to 256GB (not included)
Alarm	No
Reset	Yes

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1 \times , UPnP, HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication, Watermark, and illegal login lock
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth

System Specifications

PoE	Standard (IEEE 802.3af)	
Analytics	Motion detection, region entrance/exiting/intrusion detection (people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection, face detection, face capture.	
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection	
Alarm Events	FTP upload, email upload	

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	7.0W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	less than 95% (non-condensing)
Unit dimensions	3.72" (ф) x 3.26" (H)
Unit Weight	1.01 lbs
Certifications	FCC



*with compatible Speco Blue recorder

** Compliant with NDAA Section 889 Part B Guidelines



Optional Accessories





Power Supply





Pole Mount



O5VLWMJG Wall Mount

Cameras Interfaces















12.95W

PoE Injector



Mobile







