

# 4MP Intensifier® IP Turret Camera with Advanced Analytics

# **04iT1M**

2.8-12mm motorized lens, dark gray housing















# IP 4 TRUE INT MARKET H.265 DAY NIGHT POE SLOT IP67

#### **Features**

- Intensifier® Technology captures in full color in extreme low-light scenes
- Captures up to 4MP @ 30fps real time
- True WDR operation
- Micro SD card slot (card not included)
- Conformant with ONVIF Profile G,S,T
- IP67 Weather Resistance

- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection\*
- Face/Person/Vehicle detection\*
- NDAA Compliant\*\*
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty





Included Junction Box

# **Camera Specifications**

Image Sensor       Progressive scan 1/1.8"CMOS         Maximum Resolution       2560 × 1440 (4MP)         Field of View       Horizontal: 110°~48°; vertical: 57°~27°; diagonal: 130°~56°         Minimum Illumination       0.001 lux@F1.3, AGC ON         White Balance       Auto, Indoor, Outdoor, Manual         Compensation       True WDR (120dB), BLC, HLC         Electronic Shutter Speed       1s ~ 1/100000s         DNR       3D DNR         Angle Adjustment       Pan: 0° ~ 360°; Tilt: 0° ~ 80°; Rotation: 0° ~ 360°		
Field of View  Horizontal: 110°~48°; vertical: 57°~27°; diagonal: 130°~56°  Minimum Illumination  0.001 lux@F1.3, AGC ON  White Balance  Auto, Indoor, Outdoor, Manual  Compensation  True WDR (120dB), BLC, HLC  Electronic Shutter Speed  1s ~ 1/100000s  DNR  3D DNR	Image Sensor	Progressive scan 1/1.8"CMOS
diagonal: 130°~56°  Minimum Illumination  0.001 lux@F1.3, AGC ON  White Balance Auto, Indoor, Outdoor, Manual  Compensation  True WDR (120dB), BLC, HLC  Electronic Shutter Speed 1s ~ 1/100000s  DNR  3D DNR	Maximum Resolution	2560 × 1440 (4MP)
White Balance Auto, Indoor, Outdoor, Manual  Compensation True WDR (120dB), BLC, HLC  Electronic Shutter Speed 1s ~ 1/100000s  DNR 3D DNR	Field of View	·
Compensation True WDR (120dB), BLC, HLC  Electronic Shutter Speed 1s ~ 1/100000s  DNR 3D DNR	Minimum Illumination	0.001 lux@F1.3, AGC ON
Electronic Shutter Speed 1s ~ 1/100000s  DNR 3D DNR	White Balance	Auto, Indoor, Outdoor, Manual
DNR 3D DNR	Compensation	True WDR (120dB), BLC, HLC
	Electronic Shutter Speed	1s~1/100000s
Angle Adjustment  Pan: 0° ~ 360°; Tilt: 0° ~ 80°; Rotation: 0° ~ 360°	DNR	3D DNR
	Angle Adjustment	Pan: 0° ~ 360°; Tilt: 0° ~ 80°; Rotation: 0° ~ 360°

### **Video Specifications**

Main Resolution	2560×1440/2304×1296/1920x1080/1280x720/D1/ CIF/480×240 @30fps
Sub Stream	1280x720/D1/CIF/480×240 @30fps
Third Stream	D1/CIF/480×240 @30fps
Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Intensifier Preset, Exposure, Gain, Corridor Pattern, Image flip/mirror
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)
Multiple Streaming	3 streams

#### **Network Specifications**

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, $802.1x$ , UPnP, HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth

POEINJ	PSW5
12.95W	12VDC
D F 1 1 1	n c













### **Client Specifications**

Web Browser Support	Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari
PC Application	SecureGuard® VMS and SecureGuard CMS
Mobile	SecureGuard Client, Speco Blue

# **Audio Specifications**

A to all of opening and its	
Audio Codec	G.711 A / G.711 U
Audio Input	Built-In Mic and 3.5mm Input
Audio Output	No

Interfaces	
Ethernet	RJ45 Jack, 10/100 Mbps, PoE
Power	12VDC input jack
Audio	Built-in mic and 3.5mm Input
Card Slot	MicroSD, up to 256GB (not included)
Alarm	No
Reset	Yes

### **System Specifications**

7	
PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, Object abandoned/missing detection, region entrance/exiting/intrusion detection (human/vehicle classification), line crossing detection (human/vehicle classification), video tampering detection, scene change detection, face detection.
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection
Alarm Events	FTP upload, email upload
Image Settings	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction

## **Operating & Unit Specifications**

Power	PoE, 12VDC (power supply not included)
Power Consumption	3.5W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	Less than 95% (non-condensing)
Unit Dimensions	4.39" (φ) x 3.92" (H)
Unit Weight	1.46 lbs
Certifications	FCC



- \*with compatible Speco Blue recorder
- \*\* Compliant with NDAA Section 889 Part B Guidelines









