



# 6MP IP Dome Camera with Advanced Analytics

## O6D1M

2.8-12mm motorized lens, white housing

### Features

- Supports up to 6MP @ 30fps
- 4x Optical Zoom
- Two-way Audio Support
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 165 FT (depending on scene reflection)
- Micro SD slot up to 256GB (card not included)
- True WDR (wide dynamic range) operation
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included (works with NPT/BSP specifications)



Included Junction Box



### Camera Specifications

|                          |  |
|--------------------------|--|
| Image Sensor             | Progressive scan 1/2.5" CMOS, 6MP          |
| Maximum Resolution       | 3296 x 1856                                |
| Field of View            | 108° - 36°(H), 57° - 20°(V), 129° - 42°(D) |
| Minimum Illumination     | 0.008 lux @ F1.6, AGC ON; 0 lux with IR    |
| Day/Night                | Smart IR                                   |
| White Balance            | Auto, Indoor, Outdoor, Manual              |
| Compensation             | True WDR (120dB), BLC, HLC                 |
| Electronic Shutter Speed | 1/4 - 1/100000 sec.                        |
| DNR                      | 3D DNR                                     |

### System Specifications

|                |   |
|----------------|---|
| PoE            | Standard (IEEE 802.3af)   |
| Analytics      | Motion, exception, line crossing, region intrusion, object detection, vehicle/people detection, face detection, people/vehicle counting, loitering, tampering detection, and heat map |
| Alarm Triggers | Analytics, SD card error  |
| Alarm Events   | FTP upload, email upload  |
| Image Settings | Watermark, IP address filtering, video mask, password protection  |

### Interface

|                  |                                     |
|------------------|-------------------------------------|
| Ethernet         | 10/100 Mbps RJ45 (PoE)              |
| Video            | CVBS output (BNC x 1)               |
| Power            | DC jack                             |
| Microphone Input | Mono 3.5mm + built-in mic           |
| Audio Output     | Mono 3.5mm                          |
| Card Slot        | MicroSD, up to 256GB (not included) |
| Alarm            | 1CH alarm input, 1 CH alarm output  |
| Reset            | Yes                                 |

### Audio Specifications

|             |                 |
|-------------|-----------------|
| Audio Codec | G.711A / G.711U |
|-------------|-----------------|

### Network Specifications

|              |   |
|--------------|---|
| Protocols    | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS |
| DDNS support | Speco DDNS (free of charge)   |
| Security     | User ID & password protection, IP/Mac address filtering, digest authentication            |
| User Access  | Max. 10 simultaneous users, actual number of users may vary depending on bandwidth        |

### Video Specifications

|                    |  |
|--------------------|--|
| Main Resolution    | 2688x1520 / 3296x1856 / 3200x1800<br>2880x1624 / 1920x1080 / 1280x720<br>D1 / UGA / CIF @ 30fps  |
| Sub Stream         | 720P / D1 / UGA / CIF / 480x240 @ 30fps  |
| Third Stream       | D1 / CIF / 480x240 @ 30 fps  |
| Compression        | H.265, H.264 (HP/MP/BP), MJPEG (substream only)  |
| Video Settings     | Region of interest, privacy masking, brightness, contrast, hue, saturation, denoise, antiflicker, day/night mode, infrared settings, exposure, gain, corridor pattern, image flip/mirror |
| Bitrate Control    | VBR, CBR (64Kbps - 10Mbps)   |
| Multiple Streaming | 3 streams  |

### Client Specifications

|                     |   |
|---------------------|---|
| Web Browser Support | Google Chrome, Edge, Safari, Fire Fox, Windows (Internet Explorer 8 and up) |
| PC Application      | Speco Blue VMS, SecureGuard® CMS  |
| Mobile              | SecureGuard® Client, Speco Blue (iPhone® and Android®)                      |

## Operating & Unit Specifications

|                       |  |
|-----------------------|--|
| Power                 | PoE, 12VDC (power supply not included) |
| Power Consumption     | < 10W                                  |
| Operating Temperature | -22°F - 140°F                          |
| Operating Humidity    | Less than 95 % (non-condensing)        |
| Unit Dimensions       | 5.55" (φ) x 4.01" (H)                  |
| Unit Weight           | 1.96 lb.                               |
| Certifications        | FCC, UL Listed.                        |

| D.O.R.I (m)             | (wide)      | (telephoto)  |
|-------------------------|-------------|--------------|
| Detection (25px/m)      | 218ft (66m) | 669ft (204m) |
| Observation (63px/m)    | 87ft (27m)  | 269ft (82m)  |
| Recognition (125px/m)   | 44ft (13m)  | 135ft (41m)  |
| Identification(250px/m) | 23ft (7m)   | 66ft (20m)   |

\*With compatible Speco Silver Recorder  
 \*\*Products are in compliance with NDAA Section 889 Part B Guidelines

## Optional Accessories



**POEINJ**  
25.5W  
PoE Injector



**PSW5**  
12VDC  
Power Supply



**CMT1**  
Corner Mount



**PMT1**  
Pole Mount



**CLTX1**  
Ceiling Mount  
4" Extension



**CLTX2**  
Ceiling Mount  
8" Extension



**CLT3**  
Ceiling Mount



**WMT1**  
Wall Mount



**FMT3**  
Flush Mount

## Cameras Interfaces



3.5mm  
Audio In



3.5mm  
Audio Out



DC 12V



RJ45 PoE



Built-in mic



CVS Out



Alarm In/Out



MicroSD  
up to 256GB



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. This product has earned the UL Listed Mark. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 7/24/24

