

8MP (4K) Flexible Intensifier[®] IP Turret Camera with Advanced Analytics, NDAA

Interfaces

INT

O8FT1M

2.8-12mm motorized lens, dark gray housing

Features

-

- Flexible Intensifier® Technology to fit any lighting application
- Captures up to 8MP @ 30fps real time • Captures color in extreme low light conditions and
- monochrome in absolute darkness.
- IR range: up to 164' (depending on scene reflection)
- True WDR operation

. . . .

Micro SD card slot (card not included)

- Conformant with ONVIF Profile G/S/T
- IP67 Weather Resistance
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection*
- Face/Person/Vehicle detection*
- Junction box included • 5 year warranty



8 WDR [★] Jay Might Analytics POE SLOT IP67

| Camera Specifications | |
|--------------------------|--|
| Image Sensor | Progressive scan 1/1.8"CMOS |
| Maximum Resolution | 3840 × 2160 |
| Field of View | Horizontal: 108° ~ 45.5°; Vertical: 58° ~ 25.5°; Diagonal: 130° ~ 53° |
| Minimum Illumination | 0.006 lux@F1.4, AGC ON; 0 lux with IR |
| White Balance | Auto, Indoor, Outdoor, Manual |
| Compensation | True WDR (120dB), BLC, HLC |
| Day/Night | Smart IR |
| Electronic Shutter Speed | 1/2 - 1/100000 sec. |
| DNR | 3D DNR |
| Angle Adjustment | Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360° |
| | |

Video Specifications

Audio Specifications Audio Compression

Client Specifications

Web Browser Support

Audio input

Audio output

PC Application Mobile

| · · · · · · · · · · · · · · · · · · · | |
|---------------------------------------|---|
| Main Resolution | 8MP/6MP/4MP/2K/3MP/1080p, 2560×1440, 2304×1296, 1920x1080, 1280x720, D1, CIF, 480×240 @30fps |
| Substream | 1080p, 720p, D1, CIF, 480×240 @30fps |
| Third Stream | D1, CIF, 480×240 @30fps |
| Compression | Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG |
| Bitrate Control | VBR, CBR (64Kbps ~ 8Mbps) |
| Multiple Streaming | 3 streams |
| Video Settings | Region of Interest, Privacy masking, Brightness, Contrast, Hue, Satura- tion, Denoise, Antiflicker, Day/Night mode, Exposure, Gain, Corridor Pattern, Image flip/mirror |

G.711A / G.711U

No

Apple Safari

Built-in mic and 3.5mm input

Google Chrome, Microsoft Edge, Internet Explorer,

SecureGuard® VMS and SecureGuard CMS

SecureGuard® App, Speco Blue

| Ethernet | RJ45 Jack, 10/100 Mbps, PoE | |
|---------------------------------|---|--|
| Power | 12VDC input jack | |
| Audio | Built-in mic and 3.5mm input | |
| Card slot | MicroSD, up to 256GB (not included) | |
| Alarm | No | |
| Reset | Yes | |
| Network Specifications | | |
| Protocols | UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1 x, UPnP, HTTP, HTTPS | |
| DDNS support | Speco DDNS (free of charge) | |
| Security | User ID & Password protection, IP/MAC address filtering, digest authentication | |
| User Access | Max. 10 simultaneous users | |
| USEF ACCESS | Actual number of users may vary depending on bandwidth | |
| System Specifications | | |
| PoE | Standard (IEEE 802.3af) | |
| Analytics | Motion detection, Object abandoned/missing detection, region entrance/exiting/intrusion detection (people/vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection, face detection, face capture. | |
| Alarm Triggers | Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection | |
| Alarm Events | FTP upload, email upload | |
| Image Settings | Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction | |
| Operating & Unit Specifications | | |
| Power | PoE, 12VDC (power supply not included) | |
| Power Consumption | 10.5W (max) | |
| Operating Temperature | -40°F - 140°F | |
| Operating Humidity | less than 95% (non-condensing) | |
| Unit dimensions | 4.39″ (φ) × 3.92″ (H) | |
| Unit Weight | 1.45 lbs | |
| Certifications | FCC | |
| | * with compatible Speco Blue recorder | |

Optional Accessories





*with compatible Speco Blue recorder ** Compliant with NDAA Section 889 Part B Guidelines



Micro

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/9/23

🖆 App Stoce Play and app store On VIF* 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

speco technologies