

Seven Zone 260 Watt Commercial Amplifier

PL260A 260W commercial amplifier

Features

- Seven front-selectable 70/25V speaker zones with selectable 70/25V switch
- 24 Volt input for emergency backup power
- Separate bass and treble controls
- Each XLR microphone input has a phantom power toggle
- Mic1 selectable priority paging



rear of unit

Specifications

- RMS Output Power..... 260W
- Max. Output Power..... 390W
- AC Power Consumption.... 1200W
- Power Supply AC 117V, 60Hz, DC 24V, 12A
- Zones..... 7
- Speaker Outputs..... 4/8/16 Ohms (non-zoned), 70/25V (zoned)
- Other Outputs..... Aux (Stereo RCA), Pre-Amp (RCA)
- Inputs..... 5 x Mic (XLR), 3 x Aux (Stereo RCA),
1 x EQ/Mix (RCA), 1 x TEL (Terminal)
- Frequency Response 50Hz ~ 15KHz (±3dB)
- Tone Control Bass ± 10 dB, Treble ± 10dB
- THD Less than 1% @1KHz
- Signal/Noise Ratio..... Microphone: >60dB, TEL: >60dB, Line: >70dB
- Controls Volume for each source, Master Volume,
TEL Input Level, MoH Volume, Tone,
Zone Selector, Phantom Power on/off
- Telephone TEL in and MoH Out
- Indicators Power, power level
- Dimensions..... 16.9" (W) x 3.5" (H) x 11.6" (D)
- Weight 29.2 lbs.
- Listings UL, cUL, CE, FCC, RoHS

Optional Accessory



PBMRK2
Rack Mounting Kit

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/17/14