

## Series 25 In-Ceiling Speaker Line

**SP525C** 5.25" in-ceiling speaker

**SP625C** 6.5" in-ceiling speaker

### Features

- Stylish baffle design
- Pivoting tweeter



sold in pairs

Specifications	SP525C	SP625C
RMS Power .....	30W	40W
Max. Power.....	60W	80W
Termination Type .....	Press Terminal	Press Terminal
Sensitivity (1W/1M).....	87dB	89dB
Maximum SPL (Pmax/1M).....	94.3dB	95.5dB
Driver Impedance .....	8 Ohms	8 Ohms
Magnet.....	10 oz. ferrite	11.6 oz. ferrite
Frequency Response Range...	70Hz ~ 20Hz	50Hz ~ 20Hz
Dispersion @ 1000Hz .....	85° conical	85° conical
Driver .....	5.25" Polypropylene woofer 0.75" Silk tweeter	6.5" Polypropylene woofer 1" Silk tweeter
Speaker Dimensions .....	8" (Dia.) x 4" (D)	9.25" (Dia.) x 4.25" (D)
Mounting Dimensions.....	6.6" (Dia.)	7.75" (Dia.)
Minimum Mounting Depth.....	3.5"	3.75"
Weight .....	2.4 lbs.	3 lbs.
Material.....	Baffle: ABS Grille: Metal	Baffle: ABS Grille: Metal
Color .....	White	White

### Optional Accessories



**BRC5**  
Mounting Bracket  
(use with SP525C)



**BRC6**  
Mounting Bracket  
(use with SP625C)

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/28/14