

Active HD-TVI Video with Power Balun over Coax

TVICOAXVP

Features

- Supports up to 5MP HD-TVI
- Supports HD-TVI, AHD, HD-CVI video formats
- HD-TVI Signal extension up to 984' (300M)
- Frequency and brightness adjustable



Specifications	Transmitter	Receiver
Support		
Video Format	HD-TVI, AHD, HD-CVI, CVBS	
Max. Transmission Distance	1312' (400M)	
Ports & Interfaces		
Video Input	1 x BNC (1 Vp-p, 75 Ω)	1 x BNC (1 Vp-p, 75 Ω)
Video Output	1 x BNC (1 Vp-p, 75 Ω)	1 x BNC (1 Vp-p, 75 Ω)
Power Interface	1 x DC Jack	1 x DC Jack
Power		
Power Input	n/a	DC 24V to 40V
Power Output	12V	n/a
Ambient Temperature		
Operation	32 to 158°F (0 to 70°C)	
Storage	-4 to 185°F (-20 to 85°C)	
Humidity	Up to 95%	
Physical Characteristics		
Dimensions	1.9 x 4.4 x 1" (49.2 x 112.5 x 25.2mm)	1.9 x 4.4 x 1" (49.2 x 112.5 x 25.2mm)
Weight	0.33 Lbs (150g)	0.33 Lbs (150g)

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/14/22

Apps available from the following:



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

